




## Cable connector V3S-GM-BK5M-PVC-U

- Degree of protection IP68
- UL listed for USA and Canada
- Specific design protects against loosening and inaccurate installation

Male cordset single-ended M8 straight A-coded, 3-pin, PVC cable black, UL approved



### Dimensions



### Technical Data

#### General specifications

|                   |  |                  |
|-------------------|--|------------------|
| Connector 1       |  |                  |
| Connection        |  | plug             |
| Construction type |  | M8               |
| Style             |  | straight         |
| Locking           |  | screw connection |
| Number of pins    |  | 3                |
| Coding            |  | A-coded          |
| Connector 2       |  |                  |
| Connection        |  | cable end        |

#### Electrical specifications

|                   |       |                        |
|-------------------|-------|------------------------|
| Operating voltage | $U_B$ | max. 48 V AC / 60 V DC |
| Operating current | $I_B$ | max. 3 A               |

#### Conformity

|                      |  |                                    |
|----------------------|--|------------------------------------|
| Degree of protection |  | EN 60529                           |
| Plug connection      |  | connector M8 x 1 : IEC 61076-2-104 |
| Flammability         |  | UL 1581 , IEC 60332-1-2            |

Release date: 2022-03-19 Date of issue: 2022-03-19 Filename: 240807-100013\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

## Technical Data

### Approvals and certificates

|                |  |                                                   |
|----------------|--|---------------------------------------------------|
| UL approval    |  | AWM STYLE 2095 AWM I/II A/B 80°C 300V FT1 (cable) |
| UL File Number |  | E231213                                           |

### Ambient conditions

|                     |  |                                |
|---------------------|--|--------------------------------|
| Ambient temperature |  |                                |
| Plug connector      |  | -40 ... 90 °C (-40 ... 194 °F) |
| Cable, fixed        |  | -25 ... 80 °C (-13 ... 176 °F) |
| Cable, flexing      |  | -5 ... 80 °C (23 ... 176 °F)   |
| Pollution degree    |  | 3                              |

### Mechanical specifications

|                        |   |                                                              |
|------------------------|---|--------------------------------------------------------------|
| Plug connector         |   |                                                              |
| Tightening torque      |   | 0.4 Nm                                                       |
| Loosening protection   |   | available                                                    |
| Tool installation      |   | straight knurling and hexagon nut SW = 9 mm                  |
| Mating cycles          |   | min. 100                                                     |
| Degree of protection   |   | IP68                                                         |
| Cable                  |   | according to IEC/EN 60228 (DIN VDE 0295) class 5             |
| Sheath diameter        |   | 4.3 mm                                                       |
| Bending radius         |   | > 15 x cable diameter, moving<br>> 5 x cable diameter, fixed |
| Sheath stripping force |   | max. 50 N / 300 mm                                           |
| Sheath color           |   | black (similar to RAL 9005)                                  |
| Number of cores        |   | 3                                                            |
| Core cross section     |   | 0.34 mm <sup>2</sup>                                         |
| Cores color            |   | Core 1: brown<br>Core 3: blue<br>Core 4: black               |
| Core construction      |   | 19 x 0.15 mm Ø                                               |
| Length                 | L | 5 m                                                          |
| Cable code             |   | Li YY 3 x 0,34                                               |

### Material

|                  |  |                             |
|------------------|--|-----------------------------|
| Plug connector   |  |                             |
| Screw connection |  | Zinc diecast, nickel-plated |
| Body             |  | TPU, black                  |
| Contact surface  |  | Au                          |
| Flammability     |  | V-2                         |
| Cable            |  |                             |
| Sheathing        |  | PVC                         |
| Core insulation  |  | PVC                         |
| Flammability     |  | FT1                         |

## Connection Assignment



|   |   |    |
|---|---|----|
| 1 | — | BN |
| 3 | — | BU |
| 4 | — | BK |

**Accessories**

|                                                                                   |                          |                                            |
|-----------------------------------------------------------------------------------|--------------------------|--------------------------------------------|
|  | <b>MH V3-SCREWDRIVER</b> | torque screwdriver (0.4 Nm)                |
|  | <b>MH V3-BIT M8</b>      | plug-in cap for M8                         |
|  | <b>V1/V3-LABELHOLDER</b> | Label holder                               |
|  | <b>V1/V3-LABEL</b>       | Label plate                                |
|  | <b>MH V3-Holder</b>      | Modular universal holder for M8 connectors |