Z-Communications, Inc.
9939 Via Pasar • San Diego, CA 92126
TEL (619) 621-2700 FAX (619) 621-2722

V582ME06

VOLTAGE CONTROLLED OSCILLATOR

Rev A1



PHASE NOISE (1 Hz BW, typical)



FEATURES

- Frequency Range: 1061 - 1063 MHz
- Tuning Voltage: 1.5-4.0 Vdc
- MINI-14MS - Style Package

APPLICATIONS

- Digital Radios
- Satellite Communications
- Basestations

PERFORMANCE SPECIFICATIONS	VALUE	UNITS
Oscillation Frequency Range	1061 - 1063	MHz
Phase Noise @ 10 kHz offset (1 Hz BW, typ.)	-111	dBc/Hz
Harmonic Suppression (2nd, typ.)	-30	dBc
Tuning Voltage	1.5-4.0	Vdc
Tuning Sensitivity (avg.)	20	MHz/V
Power Output	2±3	dBm
Load Impedance	50	Ω
Input Capacitance (max.)	100	pF
Pushing	<1.5	MHz/V
Pulling (14 dB Return Loss, Any Phase)	<2.5	MHz
Operating Temperature Range	0 to 80	°C
Package Style	MINI-14MS	
POWER SUPPLY REQUIREMENTS		
Supply Voltage (Vcc, nom.)	5	Vdc
Supply Current (Icc, typ.)	22	mA

All specifications are typical unless otherwise noted and subject to change without notice.

APPLICATION NOTES

- AN-100/1 : Mounting and Grounding of VCOs
- AN-102 : Proper Output Loading of VCOs
- AN-107 : How to Solder Z-COMM VCOs

NOTES:

© Z-Communications, Inc.

All rights reserved

TUNING CURVE, typ.



POWER CURVE, typ.



PHYSICAL DIMENSIONS

