NON-ISOLATED DC/DC CONVERTERS

12V Input / 1.0 – 5.0V Output / 10A

BP02V7PB-10A

V7PB-10A Series

- Nonisolated
- Industry standard pinout
- Fixed frequency
- High efficiency means less power dissipation
- Optimized for cost
- Remote on/off
- Remote sense
- Undervoltage lockout
- Over current and short circuit protection
- Overtemperature shutdown



Description

The Bel V7PB-10A series modules are non-isolated, step down DC/DC power converters that operate from a nominal 12V source. These converters are available in a range of output voltages from 1.0V to 5.0V. They are packaged in an industry standard single-in-line footprint and provide a maximum 10A output. Standard features include remote on/off, remote sense, over current and short cicuit protection, overtemperature shutdown and output voltage adjust. Remote on/off logic is an optional feature. These products may be used almost anywhere low-voltage silicon is employed and a 12V source is available. Typical applications include file servers, routers, line cards and other computing and communications equipment.

Applications

- Telecommunications
- Networking
- Computers and peripherals

Options

- Remote on/off logic

Part Number Selection

Output Voltage	Input Voltage	Max. Output Current	Max. Output Power	Typical Efficiency	Part Number	Part Number Active Low Option
5.0V	12V	10A	50W	94%	V7PB-10A50S	V7PB-10A50L
3.3V	12V	10A	33W	92%	V7PB-10A33S	V7PB-10A33L
2.5V	12V	10A	25W	90%	V7PB-10A25S	V7PB-10A25L
2.0V	12V	10A	20W	88%	V7PB-10A20S	V7PB-10A20L
1.8V	12V	10A	18W	87%	V7PB-10A18S	V7PB-10A18L
1.5V	12V	10A	15W	86%	V7PB-10A15S	V7PB-10A15L
1.2V	12V	10A	12W	83%	V7PB-10A12S	V7PB-10A12L
1.0V	12V	10A	10W	82%	V7PB-10A10S	V7PB-10A10L

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Absolute Maximum Ratings

Parameter	Symbol	Min	Typical	Max	Unit
Continuous Input Voltage	Vin	-0.3		15	V
Output Enable Terminal Voltage	Vouten	-0.3		15	V
Ambient Temperature	Tamb	-40		85	°C
Storage Temperature	Tstor	-40		125	°C

Note: Use beyond the maximum ratings may cause a reliability degradation of the DC/DC converter or may permanently damage the device.

Input Specifications

Parameter	Symbol	Min	Typical	Max	Units
Operating Input Voltage	Vin	10.8		13.2	V
Input Current	Iin			5.5	A
No Load Input Current				60	mA
Remote Off Input Current			3	15	mA
Input Reflected Ripple Current[1]				120	mA_{rms}
Input Reflected Ripple Current (P-P)[1]				300	mApk
I^2t Inrush Current Transient			0.08	0.12	A^2s
Turn On Voltage Threshold			9.7		V
Turn Off Voltage Threshold		8.0	8.8	10.0	V

Note: Input capacitance 22µF tantalum.
1. With simulated source impedance of 800nH, 5Hz to 20MHz.

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Output Specifications

Parameter	Module	Symbol	Min	Typical	Max	Units
Output Voltage Set Point[1]		Vout				V
	5.0V		4.900	5.0	5.100	
	3.3V		3.247	3.3	3.353	
	2.5V		2.460	2.5	2.540	
	2.0V		1.968	2.0	2.032	
	1.8V		1.771	1.8	1.829	
	1.5V		1.476	1.5	1.524	
	1.2V		1.181	1.2	1.219	
	1.0V		0.984	1.0	1.016	
Load Regulation						mV
	5.0V			10	20	
	3.3V			6	16	
	2.5V			6	12	
	2.0V			5	10	
	1.8V			5	9	
	1.5V			3	7	
	1.2V			3	6	
	1.0V			3	5	
Line Regulation						mV
	5.0V			2	10	
	3.3V			2	10	
	2.5V			2	8	
	2.0V			2	6	
	1.8V			2	5	
	1.5V			2	5	
	1.2V			2	5	
	1.0V			2	5	
Regulation Over Temperature -40° to +85° C						mV
	5.0V			17	35	
	3.3V			15	30	
	2.5V			12	25	
	2.0V			11	22	
	1.8V			10	20	
	1.5V			9	18	
	1.2V			8	16	
	1.0V			7	15	
Total Output Voltage Regulation						mV
	5.0V			29	65	
	3.3V			23	56	
	2.5V			20	45	
	2.0V			18	38	
	1.8V			17	34	
	1.5V			14	30	
	1.2V			13	27	
	1.0V			12	25	

Note: All specifications are typical at nominal input, full load at 25° C unless otherwise stated.
1. Vin = 12V, Iout = full load, Ta = 25° C.

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Output Specifications

Parameter	Module	Symbol	Min	Typical	Max	Units
Output Ripple and Noise[2]	5.0V 3.3V 2.5V 2.0V 1.8V 1.5V 1.2V 1.0V			50 45 40 30 30 30 25 20	75 60 55 45 45 45 40 35	mVp-p
Output Ripple and Noise[2]	5.0V 3.3V 2.5V 2.0V 1.8V 1.5V 1.2V 1.0V			17 14 10 9 8 6 5 5	25 22 15 15 12 10 8 8	mVrms
Output Current Range	All	Iout	0		10	A
Output DC Current Limit	All	Ioutlim	13		22	A
Short Circuit Surge	All	Ioutsurge		0.8	1.5	A^2s
Turn on Time	All	Ton			80	ms
Overshoot at Turn On	All			0	3	%
Output Capacitance	All	Cout	0		3300	µF

Note: All specifications are typical at nominal input, full load at 25° C unless otherwise stated.
2. 0 - 20MHz BW, 22µF tantalum cap on output.

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Output Specifications

Parameter	Module	Symbol	Min	Typical	Max	Units
Transient Response [3]						
ΔV 50% to 100% of Max Load	5.0V			200	250	mV
Settling Time		Ts		50	80	µs
ΔV 100% to 50% of Max Load				200	250	mV
Settling Time		Ts		50	80	µs
Transient Response [3]						
ΔV 50% to 100% of Max Load	3.3V			160	200	mV
Settling Time		Ts		50	80	µs
ΔV 100% to 50% of Max Load				160	200	mV
Settling Time		Ts		50	80	µs
Transient Response [3]						
ΔV 50% to 100% of Max Load	2.5V			180	220	mV
Settling Time		Ts		50	80	µs
ΔV 100% to 50% of Max Load				180	220	mV
Settling Time		Ts		50	80	µs
Transient Response [3]						
ΔV 50% to 100% of Max Load	2.0V			140	180	mV
Settling Time		Ts		50	80	µs
ΔV 100% to 50% of Max Load				140	180	mV
Settling Time		Ts		50	80	µs

Note: All specifications are typical at nominal input, full load at 25° C unless otherwise stated.
3. di/dt = 0.5A/uS, Vin = 12VDC, Ta = 25° C, and with a 22µF tantalum cap on output.

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Output Specifications

Parameter	Module	Symbol	Min	Typical	Max	Units
Transient Response [3]						
ΔV 50% to 100% of Max Load	1.8V			140	180	mV
Settling Time		Ts		50	80	µs
ΔV 100% to 50% of Max Load				140	180	mV
Settling Time		Ts		50	80	µs
Transient Response [3]						
ΔV 50% to 100% of Max Load	1.5V			140	180	mV
Settling Time		Ts		50	80	µs
ΔV 100% to 50% of Max Load				140	180	mV
Settling Time		Ts		50	80	µs
Transient Response [3]						
ΔV 50% to 100% of Max Load	1.2V			100	150	mV
Settling Time		Ts		50	80	µs
ΔV 100% to 50% of Max Load				100	150	mV
Settling Time		Ts		50	80	µs
Transient Response [3]						
ΔV 50% to 100% of Max Load	1.0V			100	150	mV
Settling Time		Ts		50	80	µs
ΔV 100% to 50% of Max Load				100	150	mV
Settling Time		Ts		50	80	µs

Note: All specifications are typical at nominal input, full load at 25° C unless otherwise stated.
3. di/dt = 0.5A/uS, Vin = 12VDC, Ta = 25° C, and with a 22µF tantalum cap on output.

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

General Specifications

Parameter	Module	Symbol	Min	Typical	Max	Units
Efficiency[1]	5.0V 3.3V 2.5V 2.0V 1.8V 1.5V 1.2V 1.0V	η	91 89 87 85 84 83 80 79	94 92 90 88 87 86 83 82		%
Switching Frequency	All	Fsw	180	200	220	kHz
Overtemperature Shutdown	All	Tc		130		°C
Output Voltage Trim Range[2]	All		90		110	%
Remote Sense Compensation	All				10	%
Weight	All			10		g

1. Vin=12V, full load and Ta=25° C.
2. 1V module is 95% to 110%.

Control Specifications

Parameter	Module	Symbol	Min	Typical	Max	Units
Remote On/Off	All	Vouten				V
Signal Low (Unit Off)	V7PB-10AxxS		-0.3		0.4	V
Signal High (Unit On)			2.8		13.2	V
Signal Low (Unit On)	V7PB-10AxxL		-0.3		0.4	V
Signal High (Unit Off)			2.8		13.2	V

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

BP02V7PB-10A

Efficiency Data









©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Efficiency Data









©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Ripple and Noise



Ripple and noise at full load and 12Vdc input, 5.0Vdc output, full load with an external 22µF tantalum capacitor and Ta=25° C



Ripple and noise at full load and 12Vdc input, 3.3Vdc output, full load with an external 22µF tantalum capacitor and Ta=25° C



Ripple and noise at full load and 12Vdc input, 2.5Vdc output, full load with an external 22µF tantalum capacitor and Ta=25° C



Ripple and noise at full load and 12Vdc input, 2.0Vdc output, full load with an external 22µF tantalum capacitor and Ta=25° C

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Ripple and Noise



Ripple and noise at full load and 12Vdc input, 1.8Vdc output, full load with an external 22µF tantalum capacitor and Ta=25° C



Ripple and noise at full load and 12Vdc input, 1.5Vdc output, full load with an external 22µF tantalum capacitor and Ta=25° C



Ripple and noise at full load and 12Vdc input, 1.2Vdc output, full load with an external 22µF tantalum capacitor and Ta=25° C



Ripple and noise at full load and 12Vdc input, 1.0Vdc output, full load with an external 22µF tantalum capacitor and Ta=25° C

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Transient Response

Transient response: di/dt = 0.5A/µS, external load capacitance Co = 22µF (Tantalum capacitor)



Vout=5.0V
50% to 100% load transients at 12V input and Ta=25° C



Vout=5.0V
100% to 50% load transients at 12V input and Ta=25° C



Vout=3.3V
50% to 100% load transients at 12V input and Ta=25° C



Vout=3.3V
100% to 50% load transients at 12V input and Ta=25° C

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Transient Response

Transient response: di/dt = 0.5A/µS, external load capacitance Co = 22µF (Tantalum capacitor)



Vout=2.5V
50% to 100% load transients at 12V input and Ta=25° C



Vout=2.5V
100% to 50% load transients at 12V input and Ta=25° C



Vout=2.0V
50% to 100% load transients at 12V input and Ta=25° C



Vout=2.0V
100% to 50% load transients at 12V input and Ta=25° C

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Transient Response

Transient response: di/dt = 0.5A/µS, external load capacitance Co = 22µF (Tantalum capacitor)



Vout=1.8V
50% to 100% load transients at 12V input and Ta=25° C



Vout=1.8V
100% to 50% load transients at 12V input and Ta=25° C



Vout=1.5V
50% to 100% load transients at 12V input and Ta=25° C



Vout=1.5V
100% to 50% load transients at 12V input and Ta=25° C

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Transient Response

Transient response: di/dt = 0.5A/µS, external load capacitance Co = 22µF (Tantalum capacitor)



Vout=1.2V
50% to 100% load transients at 12V input and Ta=25° C



Vout=1.2V
100% to 50% load transients at 12V input and Ta=25° C



Vout=1.0V
50% to 100% load transients at 12V input and Ta=25° C



Vout=1.0V
100% to 50% load transients at 12V input and Ta=25° C

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Thermal Considerations



Output Current vs. Local Ambient Temperature and Air Velocity

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Output Voltage Set-Point Adjustment

Trim Down Test Circuit



Trim Up Test Circuit



Output Voltage Set-Point Adjustment

V7PB-10A50x Trim Resistor Calculation

$$\text{Rtrim down} = \left(\frac{7.5\ (\text{Vo adj} - 0.8)}{\text{Vo nom} - \text{Vo, adj}} - 10\right)\ \text{Kohm}$$



$$\text{Rtrim up} = \left(\frac{6}{\text{Vo, adj} - \text{Vo nom}} - 10\right)\ \text{Kohm}$$



©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Output Voltage Set-Point Adjustment

V7PB-10A33x Trim Resistor Calculation

$$\text{Rtrim down} = \left(\frac{7.5\ (\text{Vo adj} - 0.8)}{\text{Vo nom} - \text{Vo, adj}} - 15\right)\ \text{Kohm}$$



$$\text{Rtrim up} = \left(\frac{6}{\text{Vo, adj} - \text{Vo nom}} - 15\right)\ \text{Kohm}$$





V7PB-10A25x Trim Resistor Calculation

$$\text{Rtrim down} = \left(\frac{7.5\ (\text{Vo adj} - 0.8)}{\text{Vo nom} - \text{Vo, adj}} - 20\right)\ \text{Kohm}$$



$$\text{Rtrim up} = \left(\frac{6}{\text{Vo, adj} - \text{Vo nom}} - 20\right)\ \text{Kohm}$$

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Output Voltage Set-Point Adjustment

V7PB-10A20x Trim Resistor Calculation

$$\text{Rtrim down} = \left(\frac{4.64\ (\text{Vo adj} - 0.8)}{\text{Vo nom} - \text{Vo, adj}} - 15.4\right)\ \text{Kohm}$$



$$\text{Rtrim up} = \left(\frac{3.72}{\text{Vo, adj} - \text{Vo nom}} - 15.4\right)\ \text{Kohm}$$





V7PB-10A18x Trim Resistor Calculation

$$\text{Rtrim down} = \left(\frac{4.64\ (\text{Vo adj} - 0.8)}{\text{Vo nom} - \text{Vo, adj}} - 16.9\right)\ \text{Kohm}$$



$$\text{Rtrim up} = \left(\frac{3.72}{\text{Vo, adj} - \text{Vo nom}} - 16.9\right)\ \text{Kohm}$$

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Output Voltage Set-Point Adjustment

V7PB-10A15x Trim Resistor Calculation

$$\text{Rtrim down} = \left(\frac{4.64\ (\text{Vo adj} - 0.8)}{\text{Vo nom} - \text{Vo, adj}} - 13.3\right)\ \text{Kohm}$$



$$\text{Rtrim up} = \left(\frac{3.72}{\text{Vo, adj} - \text{Vo nom}} - 13.3\right)\ \text{Kohm}$$





V7PB-10A12x Trim Resistor Calculation

$$\text{Rtrim down} = \left(\frac{1.82\ (\text{Vo adj} - 0.8)}{\text{Vo nom} - \text{Vo, adj}} - 3.16\right)\ \text{Kohm}$$



$$\text{Rtrim up} = \left(\frac{1.46}{\text{Vo, adj} - \text{Vo nom}} - 3.16\right)\ \text{Kohm}$$

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Output Voltage Set-Point Adjustment

V7PB-10A10x Trim Resistor Calculation

$$\text{Rtrim down} = \left(\frac{1.82\ (\text{Vo adj} - 0.8)}{\text{Vo nom} - \text{Vo, adj}} - 0.909\right)\ \text{Kohm}$$



$$\text{Rtrim up} = \left(\frac{1.46}{\text{Vo, adj} - \text{Vo nom}} - 0.909\right)\ \text{Kohm}$$



©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

Mechanical

V7PB-10A





Pin	Function
1	+Vo
2	+Vo
3	Remote Sense
4	+Vo
5	Ground
6	Ground
7	+Vin
8	+Vin
9	No Pin
10	Trim
11	Remote On/Off

©2003 Bel Fuse Inc. Specifications subject to change without notice. 03.03

CORPORATE

Bel Fuse Inc.
206 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

FAR EAST

Bel Fuse Ltd.
8F / 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite G7, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com