
Z-Communications, Inc.
9939 Via Pasar • San Diego, CA 92126
TEL (858) 621-2700 FAX (858) 621-2722

V846ME09

VOLTAGE CONTROLLED OSCILLATOR

Rev

PHASE NOISE (1 Hz BW, typical)



FEATURES

- Frequency Range: 3284 - 4324 MHz
- Tuning Voltage: 1-22 Vdc
- MINI-16-L - Style Package

APPLICATIONS

- Microwave Radios
- Direct Broadcast
-

PERFORMANCE SPECIFICATIONS	VALUE	UNITS
Oscillation Frequency Range	3284 - 4324	MHz
Phase Noise @ 10 kHz offset (1 Hz BW, typ.)	-90	dBc/Hz
Harmonic Suppression (2nd, typ.)	-15	dBc
Tuning Voltage	1-22	Vdc
Tuning Sensitivity (avg.)	57	MHz/V
Power Output	4±4	dBm
Load Impedance	50	Ω
Input Capacitance (max.)	50	pF
Pushing	<3	MHz/V
Pulling (14 dB Return Loss, Any Phase)	<11	MHz
Operating Temperature Range	-40 to 85	°C
Package Style	MINI-16-L	
POWER SUPPLY REQUIREMENTS		
Supply Voltage (Vcc, nom.)	12	Vdc
Supply Current (Icc, typ.)	23	mA

All specifications are typical unless otherwise noted and subject to change without notice.

APPLICATION NOTES

- AN-100/1 : Mounting and Grounding of VCOs
- AN-102 : Proper Output Loading of VCOs
- AN-107 : How to Solder Z-COMM VCOs


NOTES:

© Z-Communications, Inc.


All rights reserved

LOW COST - HIGH PERFORMANCE


TUNING CURVE, typ.



POWER CURVE, typ.



PHYSICAL DIMENSIONS



PIN CONFIGURATION
P1 Vt P2 RF Out P3 Vcc REST: GROUND

PACKAGE	H
MINI-16	0.220
MINI-16LOW	0.160
MINI-16L	0.130

NOTE: ALL DIMENSIONS ARE IN INCHES