
High Precision Foil Surface Mount Current Sensing Chip Resistors with TCR of ± 2 ppm/°C and Load Life Stability of ± 0.02 %



Any value at any tolerance available within resistance range


INTRODUCTION

Model VCS1625 is a surface mount resistor designed with 4 pads for Kelvin connection. Utilizing Vishay Bulk Metal® foil as the resistance element, it provides performance capabilities far greater than other resistor technologies can supply in a product of comparable size.

This small device dissipates heat almost entirely through the pads so surface mount users are encouraged to be generous with the board's pads and traces. Gold terminations are available on special order.

Our application engineering department is available to advise and to make recommendations. For non standard technical requirements and special applications, please contact us.

FIGURE 1 - POWER DERATING CURVE[1)]



Note:

1. Power rating at + 70 °C
   1 W on alumina substrate
   0.5 W on FR4

FEATURES

Pb-free Available

RoHS* COMPLIANT


- Temperature coefficient of resistance (TCR): ± 2.0 ppm/°C typical (- 55 °C to + 125 °C, + 25 °C ref.) (see table 1)
- Tolerance: to ± 0.1 %
- Load life stability: ± 0.02 % at 70 °C, 2000 h at rated power
- Electrostatic discharge (ESD) above 25 000 V
- Short time overload ≤ 0.005 %
- Ohmic values: 0.01 Ω to 10 Ω (for higher or lower values please contact us)
- Non inductive, non capacitive design
- Power rating: 1 W at + 70 °C (figure 1)
- Current rating: 5 A maximum
- Thermal EMF: 0.05 µV/°C typical
- Non hot spot design
- Current noise: < - 40 dB
- Rise time: 1 ns without ringing
- Voltage coefficient: < 0.1 ppm/V
- Non inductive: < 0.08 µH
- For better performances please review VCS1625Z (Z-foil) data sheet

TERMINATIONS

- Two lead (Pb)-free options are available: gold plated or tin plated
- Tin/lead plated

APPLICATIONS

Electrical Schematic




- Automatic test equipment (ATE)
- Airborne (in heads-up display systems)
- High precision instrumentation
- Electron beam recording equipment
- Electron microscopes
- Current sensing applications
- Forced balance electronic scales
- Applications that require superior frequency stability
- Military
- Medical

TABLE 1 - TOLERANCE AND TCR VS. RESISTANCE VALUE (- 55 °C to + 125 °C, + 25° Ref.)

VALUE (Ω)	TOLERANCE	TYPICAL TCR	MAXIMUM TCR
> 2R000 to 10R000	0.2 %, 0.5 %, 1 %	± 2 ppm/°C	± 5 ppm/°C
> 0R500 to 2R000	0.5 %, 1 %	± 2 ppm/°C	± 10 ppm/°C
> 0R100 to 0R500	1 %	± 2 ppm/°C	± 15 ppm/°C
> 0R050 to 0R100	1 %	± 2 ppm/°C	± 20 ppm/°C
> 0R030 to 0R050	1 %	± 2 ppm/°C	± 30 ppm/°C
> 0R010 to 0R030	1 %	± 2 ppm/°C	± 50 ppm/°C


* Pb containing materials are not RoHS compliant, exemptions may apply

FIGURE 2 - DIMENSIONS in inches (millimeters)



	INCHES	MILLIMETERS
L	0.250 ± 0.010	6.35 ± 0.25
H	0.160 ± 0.010	4.06 ± 0.25
W	0.040 maximum	1.02 maximum
A	0.080 ± 0.005	2.03 ± 0.13
B	0.040 ± 0.010	1.02 ± 0.25

FIGURE 1 - TRIMMING TO VALUES
(Conceptual Illustration)



Note: Foil shown in black, etched spaces in white

FIGURE 4 - TYPICAL TCR CURVE




TABLE 2 - PERFORMANCE SPECIFICATIONS

TEST	MIL-PRF-55342 ΔR LIMITS	TYPICAL ΔR LIMITS	MAXIMUM ΔR LIMITS
Thermal Shock 5 x (- 65 °C to + 150 °C)	± 0.10 %	± 0.005 % (50 ppm)	± 0.01 % (100 ppm)
Low Temperature Operation	± 0.10 %	± 0.005 % (50 ppm)	± 0.01 % (100 ppm)
Short Time Overload	± 0.10 %	± 0.005 % (50 ppm)	± 0.02 % (200 ppm)
High Temperature Exposure	± 0.10 %	± 0.01 % (100 ppm)	± 0.02 % (200 ppm)
Resistance to Soldering Heat	± 0.2 %	± 0.01 % (100 ppm)	± 0.03 % (300 ppm)
Moisture Resistance	± 0.20 %	± 0.01 % (100 ppm)	± 0.03 % (300 ppm)
Load Life 2000 h at 70 °C: Rated Power On Ceramic PCB	± 0.5 %	± 0.02 % (200 ppm)	± 0.04 % (400 ppm)

Note
- Measurement error 0.001 R

TABLE 3 - GLOBAL PART NUMBER INFORMATION

NEW GLOBAL PART NUMBER: Y08501R50500D9L (preferred part number format)

DENOTES PRECISION	VALUE	AER*
Y	**R** = Ω	**0** = standard part, tin/lead termination **9** = standard part, lead (Pb)-free termination **129** = gold plated **1 - 999** = custom

Y	0	8	5	0	1	R	5	0	5	0	0	D	9	W

PRODUCT CODE	RESISTANCE TOLERANCE	PACKAGING
0850 = VCS1625	**B** = ± 0.1 % **E** = ± 0.2 % **D** = ± 0.5 % **F** = ± 1.0 % **G** = ± 2.0 % **J** = ± 5.0 % **K** = ± 10.0 %	**W** = waffle pack **R** = tape and reel

FOR EXAMPLE: ABOVE GLOBAL ORDER Y0850 1R50500 D 9 W:
TYPE: VCS1625
VALUES: 1.505 Ω
ABSOLUTE TOLERANCE: ± 0.5 %
TERMINATION: tin plated (lead (Pb)-free)
PACKAGING: bulk pack

HISTORICAL PART NUMBER: VCS1625 1R5050 TCR2 D S W (will continue to be used)

VCS1625	1R50500	TCR2	D	S	W
MODEL	OHMIC VALUE	TEMPERATURE COEFFICIENT CHARACTERISTIC	RESISTANCE TOLERANCE	TERMINATION	PACKAGING
VCS1625	1.505 Ω		**B** = ± 0.1 % **E** = ± 0.2 % **D** = ± 0.5 % **F** = ± 1.0 % **G** = ± 2.0 % **J** = ± 5.0 % **K** = ± 10.0 %	**S** = lead (Pb)-free **B** = tin/lead **G** = gold plated	**W** = waffle pack **T** = tape and reel

Note

* For non-standard requests or additional values, please contact application engineering.

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.