
CUI INC
a bel group

SERIES: VFM-03 | DESCRIPTION: DC POWER LINE FILTER

FEATURES

- 3 A maximum filter
- frequency attentuation to 20 dB
- available in DIP, Chassis and DIN rail mounting options
- optimized for reducing EMI noise on DC power line



RoHS

SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
input voltage		0		80	Vdc
input current				3	A
noise attenuation	at 150 kHz ~ 1 GHz		20		dB
isolation voltage				1,500	Vdc
RoHS	yes				
operating temperature		-40		85	°C
storage temperature		-55		125	°C
storage humidity	non-condensing	5		95	%
case temperature rise	at nominal current			40	°C

Notes: 1. All specifications are measured at Ta=25°C, humidity < 75%, unless otherwise specified.

PART NUMBER KEY

VFM-03 - X

Base Number


Mounting Style:
D = board mount
T = chassis mount
DIN = DIN-rail mount

SOLDERABILITY[2]

parameter	conditions/description	min	typ	max	units
hand soldering	for 3~5 seconds	350	360	370	°C
wave soldering	see wave soldering profile			260	°C

Note: 2. For board mount models only.

WAVE SOLDERING PROFILE




MECHANICAL


parameter	conditions/description	min	typ	max	units
dimensions	board mount: 25.40 x 25.40 x 11.70 [1.000 x 1.000 x 0.461 inch]				mm
	chassis mount: 76.00 x 31.50 x 21.20 [2.992 x 1.240 x 0.835 inch]				mm
	DIN-Rail mount: 76.00 x 31.50 x 25.80 [2.992 x 1.240 x 1.016 inch]				mm
case material	aluminum alloy				
weight	board mount		15		g
	chassis mount		35		g
	DIN-rail mount		55		g

MECHANICAL DRAWING (BOARD MOUNT)

units: mm [inch]
tolerance: ±0.50[±0.020]
pin diameter tolerance: ±0.10[±0.004]
pin height tolerance: ±0.50[±0.020]

PIN CONNECTIONS	
PIN	Function
1	+Vin
2	-Vin
3	GND
4	-Vout
5	+Vout






Note:Grid 2.54*2.54mm
Recommended PCB Layout
Top View

MECHANICAL DRAWING (CHASSIS MOUNT)

units: mm [inch]
tolerance: ±0.50[±0.020]

wire range: 24~12 AWG
tightening torgue: 0.4 N*m max

PIN CONNECTIONS	
PIN	Function
1	+Vin
2	-Vin
3	GND
4	-Vout
5	+Vout




MECHANICAL DRAWING (DIN-RAIL MOUNT)

units: mm [inch]
tolerance: ±0.50[±0.020]

installed on DIN rail TS35
wire range: 24~12 AWG
tightening torgue: 0.4 N*m max

PIN CONNECTIONS	
PIN	Function
1	+Vin
2	-Vin
3	GND
4	-Vout
5	+Vout



APPLICATION CIRCUIT

Figure 1
Application Circuit





Figure 2
Non-supported Application for Module



REVISION HISTORY

rev.	description	date
1.0	initial release	12/17/2018
1.01	circuit figures updated, packaging removed	01/25/2022

The revision history provided is for informational purposes only and is believed to be accurate.

CUI INC
a bel group

Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.