

Distinctive Characteristics

Single unit construction of the bushing and case gives added protection from environmental elements.


Specially designed contact mechanism for breaking light welds.

Minimal contact bounce is achieved with specially designed interlocked switching mechanism.


Outer housing of heat resistant resin meets UL 94V-0 flammability standard and provides high arc and tracking resistance.

Solder lug and screw terminal models meet IP67 of IEC60529 Standards at front panel (dust tight and water protected for temporary immersion). Behind panel standard is IP60 (dust tight but not water protected).

Wire lead models conform fully to IP67 of IEC60529 Standards at front and behind panel (dust tight and water protected for temporary immersion). These models are epoxy sealed at the switch base and covered by an outer case for further protection from dust and water (not operable under water).



Actual Size



General Specifications

Electrical Capacity (Resistive Load)

Power Level: 6A @ 125V AC & 3A @ 250V AC or 6A @ 30V DC

Other Ratings

Contact Resistance: 10 milliohms maximum for solder lug & screw terminal models
30 milliohms maximum for wire lead terminal models
Insulation Resistance: 200 megohms minimum @ 500V DC
Dielectric Strength: 1,500V AC minimum for 1 minute minimum
Mechanical Life: 30,000 operations minimum
Electrical Life: 15,000 operations minimum
Contact Timing: Break before make
Total Travel: Alternate Action .177" (4.5mm); Momentary Action .110" (2.8mm)

Materials & Finishes

Plunger: Brass with nickel plating
Bushing & Outer Case: Fiberglass reinforced polyamide (UL94V-0 outer case)
Inner Case: Melamine
Inner Sealing Ring: Silicone rubber
Outer Sealing Ring: Natural rubber
Movable Contactor: Copper with silver plating
Movable Contacts: Silver alloy with silver plating
Stationary Contacts: Silver alloy with silver plating
Terminals: Brass with silver plating for screw lug models;
brass with tin plating for solder lug & wire lead models
Wire Lead Covers: Heat resistant polyvinyl chloride (Leads are AWG 16.)

Environmental Data

Operating Temp Range: -30°C through +70°C (-22°F through +158°F)
Humidity: 90 ~ 95% humidity for 96 hours @ 40°C (104°F)
Vibration: 10 ~ 55Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range & returning in 1 minute; 3 right angled directions for 2 hours
Shock: 50G (490m/s²) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)

Installation

Mounting Torque: 1.5Nm (13 lb•in)
Soldering Time & Temp: Manual Soldering: See Profile A in Supplement section.

Standards & Certifications

Flammability Standards: UL94V-0 outer case
Wiring Material Standards: UL AWM 1015 Recognized at Flammability VW-1;
Temperature Range -20°C ~ +105°C; Maximum Load 600V; AWG 16
CSA TEW 105 Certified at Temperature Range -20°C ~ +105° C;
Maximum Load 600V

TYPICAL SWITCH ORDERING EXAMPLE

WB **1** **2** **S** — **D** **A**

POLES	
1	SPDT

TERMINALS	
S	Solder Lug
T	Screw Lug
L	Wire Lead

CAPS	
D	.520" (13.2mm) Dia.
E	.748" (19.0mm) Dia.

CAP COLORS	
A	Black
B	White
C	Red
*D	Amber
*E	Yellow
F	Green
*G	Blue
*H	Gray

CIRCUITS

2	ON	ON
5	ON	(ON)

() = Momentary

DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

WB12S-DA

SPDT ON-ON Circuit

Black .520" (13.2mm) Dia. Cap

Solder Lug Terminals

*** Not available with cap code E**

POLES & CIRCUITS

Pole	Model	Actuator Position () = Momentary		Connected Terminals		Throw & Schematics
		Normal 	Down 	Normal 	Down 	
SP SP	WB12 WB15	ON ON	ON (ON)	1-1b 1-1b	1-1a 1-1a	SPDT

Note: Terminal numbers are not actually on wire lead models.

STANDARD WIRE COLOR SCHEME

Wire leads are covered with heat resistant vinyl in accordance to UL 1015 and CSA TEW 105 Standards for Appliance Wiring Material (AWM).





Terminal Numbers & Wire Colors			
Models	1a	1	1b
WB12L, WB15L	White	Black	Red

TYPICAL SWITCH DIMENSIONS

Solder Lug



WB15S-DA




Panel Thickness
.157" (4.0mm)

TYPICAL SWITCH DIMENSIONS

Screw Lug




WB12T-DA



Wire Lead




WB12L-DA




CAPS & CAP COLORS

D AT414
.520" (13.2mm) Diameter
 Colors Available:
 A B C D E F G H
 Material: PBT Finish: Glossy



E AT412
.748" (19.0mm) Diameter
 Colors Available:
 A B C F
 Material: Polystyrene Finish: Glossy




Cap Color Codes: **A** Black **B** White **C** Red **D** Amber **E** Yellow **F** Green **G** Blue **H** Gray

STANDARD HARDWARE

AT503M Hex Face Nut

Material:
Brass with
chrome plating




1 supplied
with each
switch



AT508 Internal Tooth Lockwasher

Material:
Steel with
zinc/chromate




1 supplied
with each
switch



AT401P O-ring

Material:
Natural
rubber



1 supplied
with each
switch

