# WL 5000

## Liquid to Air Heat Exchanger System



### WATER COOLED HEAT EXCHANGER UNITS FOR MEDICAL AND INDUSTRIAL SYSTEMS

The WL5000 is a re-circulating liquid to air heat exchanger that offers dependable, compact performance by removing large amounts of heat from a liquid circuit. The coolant is re-circulated using a high-pressure pump to assure maximum flow rate. Heat from coolant is absorbed by a radiant heat exchanger and dissipated into the ambient environment using brand name fan. Manual adjustments can be made to control flow switch. Customized features are available, however, MOQ applies.

### FEATURES

- Compact design
- Reliable operation
- Adjustable flow switch
- Bypass valve protection

### APPLICATIONS

- Medical imaging systems
- Photonics laser systems
- X-Ray scanning systems
- Semiconductor fabrication


Americas: +1.919.597.7300
Europe: +46.31.420530
Asia: +86.755.2714.1166
ets.sales@lairdtech.com
**www.lairdtech.com**


### SPECIFICATIONS

| | |
|---|---|
| **Performance** | |
| Cooling capacity[1] | 5,000 Watts |
| Flow Rate | 6.5 lpm @ 3 bar |
| **Operation** | |
| Coolant | Water or Water/Glycol |
| Operational temperature range[2] | 5°C to 40° |
| Storage temperature range (w/o coolant) | -25°C to 70°C |
| Humidity range | 20% to 80% |
| Input Voltage | 230 VAC |
| Frequency | 50/60 Hz |
| Current Draw | 2.6 Amps |
| Noise | < 67 dB(A) |
| Flow switch open | 4.0 lpm |
| Maximum forward pressure | 7.0 bar |
| **Physical** | |
| Dimensions (H x W x D) | 48.1 x 40.6 x 48.3 cm |
| Weight (w/o coolant) | 38.5 kg |
| Coolant Capacity | 5.0 L |
| Couplings | Press Fit (9 mm ID hose) |


1. Capacity rating is given at a temperature of 25°C (77°F) for the ambient air and water outlet temperature of 13°C
2. For ambient conditions outside this range, please contact Laird Technologies

Performance Curves



## ISOMETRIC DRAWINGS





## NOTES

1. Check coolant level regularly.  For optimal cooling performance, coolant level should always be above radiator fins
2. Hose selection should be of material and thickness to support pressure resistance and coolant type
3. Manual adjustments can be made to control pressure and flow rate
4. Check pump filter and dust on heat exchanger periodically for cleaning

## ORDERING INFORMATION

### PART NUMBER EXAMPLE




LAIRD-ETS-WL-5000-DATA-SHEET-101416
Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non- infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2016 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.