



X0202/A

SCR

SENSITIVE SCRS


DESCRIPTION

The UTC **X0202/A** SCR series is suitable for all applications where the available gate current is limited, such as ground fault circuit interruptors, overvoltage crowbar protection in low power supplies, capacitive ignition circuit,

FEATURES

* $I_{T(RMS)}$: 1.25A

* V_{DRM}/V_{RRM} : 600/800V



*Pb-free plating product number:
X0202L/X0202AL

ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Normal	Lead Free Plating		1	2	3	
X0202-AA3-R	X0202L-AA3-R	SOT-223	K	A	G	Tape Reel
X0202-T92-B	X0202L-T92-B	TO-92	K	G	A	Tape Box
X0202-T92-K	X0202L-T92-K	TO-92	K	G	A	Bulk
X0202-T92-R	X0202L-T92-R	TO-92	K	G	A	Tape Reel
X0202A-AA3-R	X0202AL-AA3-R	SOT-223	K	A	G	Tape Reel
X0202A-T92-B	X0202AL-T92-B	TO-92	K	G	A	Tape Box
X0202A-T92-K	X0202AL-T92-K	TO-92	K	G	A	Bulk
X0202A-T92-R	X0202AL-T92-R	TO-92	K	G	A	Tape Reel

Note: Pin Assignment: G: Gate A: Anode K: Cathode

X0202L-AA3-R (1)Packing Type (2)Package Type (3)Lead Plating		(1) B: Tape Box, K: Bulk, R: Tape Reel (2) AA3: SOT-223, T92: TO-92 (3) L: Lead Free Plating, Blank: Pb/Sn
--	--	---

■ ABSOLUTE MAXIMUM RATINGS (unless otherwise specified)

PARAMETERS		SYMBOL	RATINGS	UNIT
Peak Repetitive Forward and Reverse Blocking Voltage ($T_J=110^\circ\text{C}$, $R_{GK}=1\text{k}\Omega$)	X0202	V_{DRM} , V_{RRM}	600	V
	X0202A		800	V
RMS On-State Current 180° Conduction Angle ($T_{\text{tab}}=95^\circ\text{C}$)		$I_{\text{T(RMS)}}$	1.25	A
Average On-State Current 180° Conduction Angle ($T_{\text{tab}}=95^\circ\text{C}$)		$I_{\text{T(AV)}}$	0.8	A
Non Repetitive Surge Peak on-State Current ($t_p=8.3\text{ms}$ $T_J=25^\circ\text{C}$)		I_{TSM}	25	A
Non Repetitive Surge Peak on-State Current ($t_p=10\text{ms}$ $T_J=25^\circ\text{C}$)		I_{TSM}	22.5	A
I^2t Value for Fusing ($t_p=10\text{ms}$ $T_J=25^\circ\text{C}$)		I^2t	2.5	A^2S
Critical Rate Of Rise Of On-state Current $I_G=2 \times I_{\text{GT}}$, $t_r \leq 100\text{ns}$, $f=60\text{Hz}$, $T_J=125^\circ\text{C}$		di/dt	50	$\text{A}/\mu\text{s}$
Peak Gate Current ($p=20\mu\text{s}$ $T_J=125^\circ\text{C}$)		I_{GM}	1.2	A
Average Gate Power Dissipation ($T_J=125^\circ\text{C}$)		$P_{\text{G(AV)}}$	0.2	W
Operating Junction Temperature Range		T_J	$-40 \sim +125$	
Storage Junction Temperature Range		T_{STG}	$-40 \sim +150$	

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA







PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Tab	SOT-223	θ_{JT}	25	/W
	TO-92		60	/W
Junction to Ambient ($S=5\text{cm}$)	SOT-223	θ_{JA}	60	/W
	TO-92		150	/W

S=Copper surface under tab







■ ELECTRICAL CHARACTERISTICS ($T_J=25^\circ\text{C}$, unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Peak Forward or Reverse Blocking Current $T_J=25^\circ\text{C}$ $T_J=125^\circ\text{C}$	I_{DRM} , I_{RRM}	$V_{\text{DRM}}=V_{\text{RRM}}$, $R_{\text{GK}}=1\text{k}\Omega$			5	μA
					500	μA
Peak Forward On-State Voltage	V_{TM}	$I_{\text{TM}}=2.5\text{A}$, $t_p=380\mu\text{s}$			1.45	V
Gate Trigger Current	I_{GT}	$V_D=12\text{V}$, $R_L=140\Omega$			200	μA
Gate Trigger Voltage	V_{GT}	$V_D=12\text{V}$, $R_L=140\Omega$			0.8	V
Gate Non-Trigger Voltage	V_{GD}	$V_D=V_{\text{DRM}}$, $R_L=3.3\text{k}\Omega$, $R_{\text{GK}}=1\text{k}\Omega$, ($T_J=125^\circ\text{C}$)	0.1			V
Holding Current	I_{H}	$I_T=50\text{mA}$, $R_{\text{GK}}=1\text{k}\Omega$			5	mA
Latch Current	I_{L}	$I_G=1\text{mA}$, $R_{\text{GK}}=1\text{k}\Omega$			6	mA
Critical Rate of Rise of Off-State Voltage	dv/dt	$V_D=67\%V_{\text{DRM}}$, $R_{\text{GK}}=1\text{k}\Omega$, ($T_J=110^\circ\text{C}$)	10			$\text{V}/\mu\text{s}$
Peak Reversed Gate Voltage	V_{RG}	$I_{\text{RG}}=10\mu\text{A}$	8			V
Threshold Voltage	V_{TO}	($T_J=125^\circ\text{C}$)			0.9	V
Dynamic Resistance	R_d	($T_J=125^\circ\text{C}$)			200	$\text{m}\Omega$

■ TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS(Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.