



XFMRS, Inc.

SPECIFICATION FOR APPROVAL

XFMRS P/N : XFEB201209-330-4A				Rev: A/2		
DIMENSION : (m/m)  				A	ø2.0±0.2	m/m
				B	1.2±0.2	m/m
				C	0.9±0.2	m/m
				D	0.5±0.3	m/m
				E		m/m
				F		m/m
				G		m/m
				H		m/m
				I		m/m
				J		m/m
				K		m/m
				L		m/m
				M		m/m
				N		m/m
				O		m/m
ELECTRICAL REQUIREMENTS				TEST INSTRUMENTS		
Z	33±25% ohm	TEST FREQ.	100	MHz	☐ HP 34401A MULTIMETER ☐ HP 4195 NETWORKS/SPECTRUM ANALYZER ☐ HP 42841 BIAS CURRENT SOURCE ☐ HP 4285A LCR METER ☐ HP 4286A RF LCR METER ☒ HP 4291A RF IMPEDANCE / MATERIAL ANALYZER ☐ HP 4338A MILLION OHM METER ☐ HP 6632A DC POWER SUPPLY ☐ HP4284A PRECISION LCR METER	
Rdc	0.015 OHMS MAX	TEST FREQ.		MHz		
Idc	4000mA MAX.	TEST FREQ.		MHz		
Notes: 1. Solderability: Leads shall meet MIL-STD-202, Method 208D for solderability. 2. Flammability: UL94V-0 3. ASTM oxygen index: > 28% 4. Insulation System: Class F 155°C. UL file E151556 5. Operating Temperature Range: All listed parameters are to be within tolerance from -55°C to +125°C 6. Storage Temperature Range: -55°C to +125°C 7. Aqueous wash compatible 8. SMD Lead Coplanarity: ±0.004"(0.102mm) 9. Moisture Sensitivity: Level 3 10. Electrical and mechanical specifications 100% tested 11. RoHS Compliant Component						
DRAWN BY :		CHECKED BY :		APPROVED BY :		
BUDDY WOODS		JOE HUFF		J Ng		
PROPRIETARY Document is the property of XFMRS Group & is not allowed to be duplicated without authorization.						