


XFMRS, Inc.

SPECIFICATION FOR APPROVAL

XFMRS P/N : XFEB321611-101-3A				Rev: A/2	
DIMENSION : (m/m) 				A	3.2±0.2 m/m
				B	1.6±0.2 m/m
				C	1.1±0.2 m/m
				D	0.5±0.3 m/m
				E	m/m
				F	m/m
				G	m/m
				H	m/m
				I	m/m
				J	m/m
				K	m/m
				L	m/m
				M	m/m
				N	m/m
				O	m/m
ELECTRICAL REQUIREMENTS				TEST INSTRUMENTS	
Z	100±25% Ohms	TEST FREQ.	100	MHz	● HP 34401A MULTIMETER ○ HP 4195 NETWORKS/SPECTRUM ANALYZER ○ HP 42841 BIAS CURRENT SOURCE ○ HP 4285A LCR METER ○ HP 4286A RF LCR METER ● HP 4291A RF IMPEDANCE / MATERIAL ANALYZER ○ HP 4338A MILLION OHM METER ○ HP 6632A DC POWER SUPPLY ○ HP4284A PRECISION LCR METER
Rdc	0.035 Ohms Max	TEST FREQ.		MHz	
Idc	3000mA MAX.	TEST FREQ.		MHz	
Notes: 1. Solderability: Leads shall meet MIL-STD-202, Method 208D for solderability. 2. Flammability: UL94V-0 3. ASTM oxygen index: > 28% 4. Insulation System: Class F 155°C. UL file E151556 5. Operating Temperature Range: All listed parameters are to be within tolerance from -55°C to +125°C 6. Storage Temperature Range: -55°C to +125°C 7. Aqueous wash compatible					
DRAWN BY :					
CHECKED BY :					
APPROVED BY :					
Li Xiaofeng					
Liao					
BW					