
XTL1004

13.56000 MHz Crystal Unit

- ***Surface Mount Seam-Weld Package***
- ***Good Frequency Stability over Temperature***
- ***Excellent Reliability***
- ***Complies with Directive 2002/95/EC (RoHS)***

The XTL1004 is a surface mount 5.0 x 3.2 mm crystal unit for use in wireless telecommunications devices, especially where an ultra-miniature package is needed for mobility.




SM5032-4 Case

Electrical Characeristics

Characteristic	Sym	Notes	Minimum	Typical	Maximum	Units
Nominal Frequency				13.56000		MHz
Mode of Oscillation				Fundamental		
Storage Temperature Range			-40		+85	°C
Operating Temperature Range			-20		+70	°C
Frequency Stability over Operating Temperature Range				±10 ppm (referred to the value at 25 °C)		
Frequency Make Tolerance	F_L			±10 ppm @ 25 °C ±3 °C		
Equivalent Series Resistance	ESR				50	Ω
Nominal Drive Level				10		µW
Shunt Capacitance	C_O				3	pF
Load Capacitance	C_L			20		pF
Stanard Shipping Quantity on 330 mm (13”) Reel				3000		units
Lid Symbolization (in addition to Lot and/or Date Codes)				1004 YWWS		

Crystal Equivalent Circuit



CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.

Notes:


1. The design, manufacturing process, and specifications of this device are subject to change without notice.


©2009-2010 by RF Monolithics, Inc.

SM5032-4 Case

4-Terminal Surface-Mount Seam Weld Case

5.0 x 3.2 mm Nominal Footprint






Top View



Side View




Bottom View

Package Dimensions (mm)


Electrical Connections

Pin	Connection
1	GND
2	IN/OUT
3	GND
4	IN/OUT

Note: Pin #1 & #3 are connected to metal cap on top




Footprint (mm)




Package Orientation in Carrier Tape

©2009-2010 by RF Monolithics, Inc.

Reel Dimensions



Tape Dimensions



Notes:

1. Unless otherwise specified, tolerance on dimensions is ±0.1 mm
2. Material is black conductive polystyrene
3. 10 pitch cumulative tolerance is ±0.2 mm

©2009-2010 by RF Monolithics, Inc.