


HIGH-DENSITY 1U SERVER PLATFORM



YR190-B8228-X2

B8228Y190X2-045V4H



■ Front View



■ Back View



High-Density 1U dual-socket SMP server implementation for IPDC applications

- Dual C32 sockets support up to (2) AMD Opteron™ 4100/4200 series processors (Lisbon/Valencia)
- Support (2) HyperTransport™ 3.0 link, max. bandwidth up to 25.6 GB/s @ 6.4GT/s per link
- AMD SR5650 + SP5100
- (12) 240-pin DDR3 DIMM slots support up to 96GB R-DDR3 1333/1066/800MHz w/ ECC memory
- (1) HH/HL PCI-E (Gen.2) x16 slot
- (3) GbE LAN
- (4) Hot-swap 2.5" SATA-II HDDs w/ RAID 0, 1, 10, 5 support
- Onboard BMC w/ IPMI and iKVM support
- (1) ERP1U high-efficiency 450W PSU w/ PFC, 80-PLUS Silver Certified

YR190-B8228-X2

B8228Y190X2-045V4H

TYAN
Specifications

Top View

Easy-swap System FANs
(2) 4056 + (1) 4028

M7018-BP
BP4-port SAS/SATA-II
HDD backplane board

M5376-FPB
Integrated front panel board



ERP1U 450W PSU, 80-PLUS Silver

M7018-R16-1L
Provide (1) low-profile
PCI-E (Gen. 2) x16 slot Rear View

S8228GM3NR
(2) C32 sockets
(6+6) R-DDR3 1333/1066/800MHz
Max.96GB, (3) GbEports,
Legacy-free Rear I/O

System	Form Factor	1U Rackmount Frame w/ 2x 1U blades	Graphic (per blade)	Connector type	D-Sub 15-pin
	Chassis Name	YR190		Resolution	1600x1200@60Hz
	Dimension (H x W x D)	1.72" x 17.32" x 28.74" (43.6 x 440 x 730mm)		Chipset	Aspeed AST2050
	Motherboard	S8228GM3NR	Input / Output (per blade)	USB	(5) USB2.0 ports (2 at rear, 2 at front, 1 type A onboard)
	Gross Weight	25 kg (w/ 2 blades installed)		COM	(1) DB-9 port
Front Panel (per blade)	Buttons	(1) RST / (1) ID / (1) PWR		VGA	(1) D-Sub 15-pin VGA port
	LEDs	(1) Power / (1) BMC / (2) LAN / (1) HDD	System Monitoring (per blade)	RJ-45	(3) GbE ports
	I/O Ports	(2) USB ports		Chipset	Winbond W83795G
External Drive Bay (per blade)	Type / Q'ty	2.5" Hot-Swap / (4)		Voltage	Monitors voltage for CPU, memory, chipset & power supply
	Supported HDD Interface	SAS 3.0Gb/s (via HBA) SATA-II 3.0Gb/s		Temperature	Monitors temperature for CPU & system environment
System Cooling Configuration (per blade)	FAN	(3) 4cm fans		LED (On system front panel)	Fan fail LED indicator Over temperature warning indicator
				Others	Watchdog timer support
Power Supply (per blade)	Type	ERP1U cold-swap	Server Management (per blade)	Onboard Chipset	Onboard Aspeed AST2050
	Input Range	Full-range AC(100-240V)		AST2050 IPMI Feature	IPMI 2.0 compliant baseboard management controller (BMC) BIOS update USB 2.0 virtual hub
	Frequency	47 - 63 Hertz		AST2050 iKVM Feature	24-bit high quality video compression Dual 10/100 Mb/s MAC interfaces
	Output Watts	450 Watts	BIOS (per blade)	Brand / ROM size	AMI / 4MB
Processor (per blade)	Efficiency	PFC / 80-plus Silver		Feature	Plug and Play (PnP) PCI2.3 / WfM2.0 / SMBIOS2.3 / PXE boot ACPI 2.0 power management Power on mode after power recovery User-configurable H/W monitoring Auto-configurable of hard disk types Multiple boot options
	Supported CPU Series	AMD Opteron™ 4100/4200 series processors			
	Socket Type / Q'ty	C32 / (2)			
Memory (per blade)	Average CPU Power (ACP) wattage	Up to 50W	Operating System	OS supported list	Please refer to our OS supported list.
	System Bus	Support (2) HyperTransport™ 3.0 link, max. bandwidth up to 25.6 GB/s @ 6.4GT/s per link		FCC (DoC)	Class A
	Chipset (per blade)	Chipset	Regulation	CE (DoC)	Yes
		Supported DIMM Qty		Operating Temp.	10° C ~ 35° C (50° F~ 95° F)
Expansion Slots (per blade)		DIMM Type / Speed	Operating Environment	Non-operating Temp.	- 40° C ~ 70° C (-40° F ~ 158° F)
		Capacity		In/Non-operating Humidity	90%, non-condensing at 35° C
		Memory channel		RoHS	RoHS 6/6 Complaint
		Memory voltage			Yes
LAN (per blade)	PCI-E	(1) Low-Profile PCI-E Gen.2 x16 slot			
	Pre-installed TYAN Riser Card	M7018-R16-1L, PCI-E x16 1U riser card (right)			
Storage (per blade)	Port Q'ty	(3)			
	Controller	Intel® 82576EB Intel® 82574L			
	SATA	Controller			
		Speed			

(Specifications are subject to change without notice. Items pictured may only be representative.)

MITAC INTERNATIONAL CORP.

TYAN Business Unit

USA
Tel: +1-510-651-8868
Fax: +1-510-651-7688

Taiwan
Tel: +886-2-2652-5888
Fax: +886-2-2652-5805

Japan
Tel: +81-3-3769-8311
Fax: +81-3-3769-8328

Europe
Sales: +32 2456 1721
Technical Support: +32 2456 1722

China
Shanghai Tel: +86-21-61431188 Ext 1366
China Tel: +86-010-62555015 Ext 8302