

Coaxial

Power Splitter/Combiner

2 Way-90° 50Ω 2000 to 4200 MHz


Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.
Internal Dissipation	0.125W max.
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

SUM PORT	S
PORT 1 (0°)	1
PORT 2 (+90°)	3

Outline Drawing




Outline Dimensions (inch/mm)

A	B	C	D	E	F	G
2.00	2.00	0.75	1.00	0.25	1.500	0.125
50.80	50.80	19.05	25.40	6.35	38.10	3.18

H	J	K	L	wt
0.39	1.00	0.50	1.00	grams
9.91	25.40	12.70	25.40	170.0

electrical schematic



Features

- wideband, 2000 to 4200 MHz
- low insertion loss, 0.4 dB typ.
- good isolation, 22 dB typ.
- rugged shielded case

Applications

- balanced amplifiers
- modulators
- test set-ups





Electrical Specifications

Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Frequency		2000		4200	MHz
Insertion Loss (above theoretical 3 dB)	2000 - 4200	—	0.4	0.9	dB
Isolation	2000 - 4200	16	22	—	dB
Phase Unbalance	2000 - 4200	—	5	8	Degree
Amplitude Unbalance	2000 - 4200	—	—	1.0	dB
VSWR (Port S)	2000 - 4200	—	1.25	—	:1
VSWR (Port 1, 2)	2000 - 4200	—	1.35	—	:1

Typical Performance Data

Frequency (MHz)	Total Loss ¹ (dB)		Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1	S-2						
2000	3.36	3.44	0.08	24.21	86.71	1.30	1.12	1.14
2500	3.40	3.52	0.12	29.17	84.70	1.19	1.12	1.41
2600	3.44	3.53	0.09	28.51	85.08	1.26	1.11	1.45
2700	3.48	3.55	0.07	27.59	85.56	1.31	1.10	1.46
2800	3.51	3.56	0.05	26.63	86.18	1.33	1.08	1.44
2900	3.52	3.56	0.04	25.74	86.89	1.33	1.07	1.41
3000	3.51	3.55	0.04	24.99	87.70	1.31	1.05	1.38
3200	3.49	3.52	0.04	24.05	89.31	1.22	1.03	1.28
3400	3.46	3.48	0.01	24.21	90.88	1.11	1.07	1.16
3600	3.49	3.47	0.02	25.79	92.11	1.02	1.14	1.09
3800	3.52	3.50	0.02	30.04	93.12	1.07	1.20	1.05
4000	3.55	3.54	0.01	39.30	93.99	1.09	1.24	1.08
4100	3.57	3.56	0.00	37.06	94.22	1.09	1.25	1.11
4200	3.59	3.58	0.01	31.66	94.19	1.07	1.28	1.15

1. Total Loss = Insertion Loss + 3dB splitter loss.



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuits' applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

Mini-Circuits®

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

ZAPDQ-4+



SMA version shown

CASE STYLE: F14

Connectors	Model
N-TYPE	ZAPDQ-4-N+
SMA	ZAPDQ-4-S+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

REV. OR
M164029
ED17080801
ZAPDQ-4+
YL/CP/AM
171221