Creation Date : July 17, 2019 (GMT)

Programmable Power Supplies (CVCC)

ZUP36-12/L

RoHS

Sales Region	Worldwide
Series	ZUP
Type	400W Model
Status	Production
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics	
Input Voltage[AC]	Single-phase 100V/200V
Input Voltage Range[AC]	85 to 265V
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	36V
Output Voltage[DC]	0 to 36V
Rated Output Current	12A
Output Current	0 to 12A
Rated Output Power	432W
Efficiency	84% Typ.
Voltage Ripple Noise	0.005Vrms (5Hz to 1MHz)
Current Ripple Noise	0.015Arms (5Hz to 1MHz)

Cases Shape & Size	
Case'□ shape	Bench top
Width(W)	70mm Nom.
Height(H)	153mm Nom.
Depth(D)	405.9mm Nom.
Weight	3200g Typ.

Other	
Interface Option	Front panel output jacks
Operating Temp. Range	0 to 50°C
Safety Standard(Certified)	CSA C22.2 No.1010.1-92 EN61010-1 UL3111-1
Safety Standard(Conformed)	
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.