Creation Date : May 10, 2022 (GMT)

Programmable Power Supplies

ZUP36-6/LUW

RoHS

Sales Region	Worldwide (except Japan)
Series	ZUP
Model	ZUP 200W
Status	Production
Option Lineup	Please refer to here.
Recommended EMC Filter	
Accessories	Please refer to here.



Electrical Characteristics	
Input	Single-phase
Input Voltage Range[AC]	85 to 265Vac
Input Frequency Range	47 to 63Hz
Rated Output Voltage[DC]	36Vdc
Output Voltage[DC]	0 to 36Vdc
Rated Output Current	6A
Output Current	0 to 6A
Rated Output Power	216W
Efficiency	80% Typ.
Voltage Ripple Noise	0.005Vrms (5Hz to 1MHz)
Current Ripple Noise	0.0075Arms (5Hz to 1MHz)

Package Type & Size	
Package Type	3U Rack mount / Bench top
Width(W)	70mm Nom. (2.76in Nom.)
Height(H)	153mm Nom. (6.02in Nom.)
Depth(D)	405.9mm Nom. (15.98in Nom.)
Weight	2900g Typ. (6.4lbs Typ.)

Other	
Interfaces Included	RS-232 RS-485 Front panel output jacks IEC320 cable USA plug Serial link cable RJ-45
Interface Options	
Operating Temp. Range	0 to 50°C
Safety Standard(Certified)	EN61010-1 CSA C22.2 No.1010.1-92 UL3111-1

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.

Programmable Power Supplies

ZUP36-6/LUW

RoHS

Safety Standard(Conformed)

Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.