

ZWD100PAF-0524



Sales Region	Worldwide
Series	ZWD-PAF
Status	Production
Feature	Peak power capability
Option	
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics	
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	81% Typ.
Rated Output Voltage[DC]	<u>5V</u> <u>24V</u>
Output Voltage Range[DC]	<u>4.5 to 5.5V</u> <u>22.8 to 27.6V</u>
Minimum Output Current	
Maximum Output Current	<u>5A</u> <u>4A</u>
Maximum Average Current	
Maximum Peak Current	
Total Maximum(Average) Output Power	100W
Total Maximum Peak Power	196W

Cases Shape & Size	
Case'□ shape	PC board
Width(W)	75mm Nom.
Height(H)	35mm Nom.
Depth(D)	222mm Nom.
Weight	460g Typ.

Other	
Operating Temp. Range	-10 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
	EN50178
Safety Standard(Conformed)	Den-an

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.