


ZWD150PAF-0524/J



Sales Region	Worldwide
Series	ZWD-PAF
Status	Production
Feature	Peak power capability
Option	JST connector type
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics	
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	82% Typ.
Rated Output Voltage[DC]	<u>5V</u> <u>24V</u>
Output Voltage Range[DC]	<u>4.5 to 5.5V</u> <u>22.8 to 27.6V</u>
Minimum Output Current	
Maximum Output Current	<u>5A</u> <u>6A</u>
Maximum Average Current	
Maximum Peak Current	
Total Maximum(Average) Output Power	150W
Total Maximum Peak Power	294W

Cases Shape & Size	
Case'□ shape	PC board
Width(W)	85mm Nom.
Height(H)	40mm Nom.
Depth(D)	222mm Nom.
Weight	530g Typ.

Other	
Operating Temp. Range	-10 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	EN60950-1
	EN50178
Safety Standard(Conformed)	Den-an

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.