
Creation Date : January 28, 2019 (GMT)

AC-DC Power Supplies

ZWD150PAF-0524/TA

RoHS Lead Free

Sales Region	Worldwide
Series	ZWD-PAF
Status	Production
Feature	Peak Load Peak power capability
Option	With cover type With terminal (Vertical) type
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics	
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	82% Typ.
Rated Output Voltage[DC]	5V 24V
Output Voltage Range[DC]	4.5 to 5.5V 22.8 to 27.6V
Minimum Output Current	
Maximum Output Current	5A 6A
Maximum Average Current	
Maximum Peak Current	
Total Maximum(Average) Output Power	150W
Total Maximum Peak Power	294W

Cases Shape & Size	
Case'□ shape	PC board
Width(W)	95mm Nom.
Height(H)	51mm Nom.
Depth(D)	252mm Nom.
Weight	885g Typ.

Other	
Operating Temp. Range	-10 to 60°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 EN60950-1 EN50178
Safety Standard(Conformed)	Den-an

Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

Copyright(c) TDK Corporation. All rights reserved.