

G100E Series

Low Cost, 1W MiniDIP Single & Dual Output DC/DC Converters



Key Features:

- 1W Output Power
- Compact "MiniDIP" Case
- UL Approved (File E245422)
- Single & Dual Outputs
- 1,000 VDC Isolation
- >3.5 MHour MTBF
- 24 Standard Models
- **LOWEST COST!!**



RoHS Compliant



MicroPower Direct
292 Page Street
Suite D
Stoughton, MA 02072
USA

T: (781) 344-8226
F: (781) 344-8481
E: sales@micropowereirect.com
W: www.micropowereirect.com



Electrical Specifications

Specifications typical @ +25°C, nominal input voltage & rated output current, unless otherwise noted. Specifications subject to change without notice.

Input

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage Range	5 VDC Input	4.5	5.0	5.5	VDC
	12 VDC Input	10.8	12.0	13.2	
	24 VDC Input	21.6	24.0	26.4	
Input Filter	Internal Capacitor				
Reverse Polarity Input Current				0.3	A

Output

Parameter	Conditions	Min.	Typ.	Max.	Units
Output Voltage Accuracy			±1.0	±3.0	%
Output Voltage Balance	Dual Output , Balanced Loads		±0.1	±1.0	%
Line Regulation	For Vin Change of 1%		±1.2		%
Load Regulation (Note 1)	See Model Selection Guide				
Ripple & Noise (20 MHz) (Note 2)			50	75	mV P - P
Output Power Protection		120			%
Temperature Coefficient			±0.02	±0.03	%/°C
Output Short Circuit	Momentary (1.0 Sec.)				

General

Parameter	Conditions	Min.	Typ.	Max.	Units
Isolation Voltage	60 Seconds	1,000			VDC
Isolation Resistance	500 VDC	1,000			MΩ
Isolation Capacitance	100 kHz, 1V		60		pF
Switching Frequency			100		kHz

Environmental

Parameter	Conditions	Min.	Typ.	Max.	Units
Operating Temperature Range	Ambient	-40	+25	+85	°C
Storage Temperature Range		-55		+125	°C
Cooling	Free Air Convection				
Humidity	RH, Non-condensing			95	%

Physical

Case Size	0.80 x 0.40 x 0.25 Inches (20.4 x 10.2 x 6.5 mm)
Case Material	Non-Conductive Black Plastic (UL94-V0)
Weight	0.07 Oz (2.1g)

Reliability Specifications

Parameter	Conditions	Min.	Typ.	Max.	Units
MTBF	MIL HDBK 217F, 25°C, Gnd Benign	3.5			MHours
Safety Standards	UL 1950, EN 60950, IEC 60950				
Safety Approvals	UL, cUL; File No. E245422				

Absolute Maximum Ratings

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage Surge (1 Sec)	5 VDC Input	-0.7		9.0	VDC
	12 VDC Input	-0.7		18.0	
	24 VDC Input	-0.7		30.0	
Lead Temperature	1.5 mm From Case For 10 Sec			300	°C
Internal Power Dissipation	All Models			450	mW

Caution: Exceeding Absolute Maximum Ratings may damage the module. These are not continuous operating ratings.

Model Selection Guide

Model Number	Input				Output			Load Regulation (% , Max)	Efficiency (% , Typ)	Fuse Rating Slow-Blow (mA)
	Voltage (VDC)		Current (mA)		Voltage (VDC)	Current (mA , Max)	Current (mA , Min)			
	Nominal	Range	Full-Load	No-Load						
G101E	5	4.5 - 5.5	278	30	5.0	200.0	20.0	15	72	500
G102E	5	4.5 - 5.5	270	30	9.0	111.0	12.0	15	74	500
G103E	5	4.5 - 5.5	260	30	12.0	83.0	9.0	15	77	500
G104E	5	4.5 - 5.5	253	30	15.0	67.0	7.0	15	79	500
G105E	5	4.5 - 5.5	278	30	±5.0	±100.0	±10.0	15	72	500
G106E	5	4.5 - 5.5	267	30	±9.0	±56.0	±6.0	15	75	500
G107E	5	4.5 - 5.5	256	30	±12.0	±42.0	±5.0	15	78	500
G108E	5	4.5 - 5.5	253	30	±15.0	±33.0	±4.0	15	79	500
G111E	12	10.8 - 13.2	114	15	5.0	200.0	20.0	15	73	200
G112E	12	10.8 - 13.2	111	15	9.0	111.0	12.0	15	75	200
G113E	12	10.8 - 13.2	105	15	12.0	83.0	9.0	15	79	200
G114E	12	10.8 - 13.2	104	15	15.0	67.0	7.0	15	80	200
G115E	12	10.8 - 13.2	113	15	±5.0	±100.0	±10.0	15	74	200
G116E	12	10.8 - 13.2	110	15	±9.0	±56.0	±6.0	15	76	200
G117E	12	10.8 - 13.2	105	15	±12.0	±42.0	±5.0	15	79	200
G118E	12	10.8 - 13.2	104	15	±15.0	±33.0	±4.0	15	80	200
G121E	24	21.6 - 26.4	56	8	5.0	200.0	20.0	15	74	100
G122E	24	21.6 - 26.4	55	8	9.0	111.0	12.0	15	76	100
G123E	24	21.6 - 26.4	52	8	12.0	83.0	9.0	15	80	100
G124E	24	21.6 - 26.4	51	8	15.0	67.0	7.0	15	81	100
G125E	24	21.6 - 26.4	56	8	±5.0	±100.0	±10.0	15	74	100
G126E	24	21.6 - 26.4	55	8	±9.0	±56.0	±6.0	15	76	100
G127E	24	21.6 - 26.4	52	8	±12.0	±42.0	±5.0	15	80	100
G128E	24	21.6 - 26.4	51	8	±15.0	±33.0	±4.0	15	81	100

Other input/output combinations are available (i.e. 3.3 VDC). Contact the factory for details at: sales@micropowerdirect.com

Notes:

- Output load regulation is specified for a load change of 10% to 100%.
- These units should not be operated with a load under 10% of full load. Operation at no-load may cause damage to the unit.
- These converters will operate without external components. However, when measuring output ripple, it is recommended that an external ceramic capacitor be placed from the +Vout pin to the -Vout pin for single output units and from each output to common for dual output units. An input capacitor will enhance stability over temperature and input line variations. Recommended capacitor values are given in the table above. For applications requiring very low output noise levels, a simple LC filter should be effective.
- Dual output units may be connected to provide a 10V, 18V, 24V or 30 VDC output. To do this, connect the load across the positive (+Vout) and negative (-Vout) outputs and float the output common.
- It is recommended that a fuse be used on the input of a power supply for protection. See the Model Selection table above for the correct rating.

Pin Connections


Pin	Single	Dual	Pin	Single	Dual
1	-Vin	-Vin	9	+Vout	+Vout
7	NC	NC	11	-Vout	-Vout
8	No Pin	Common	14	+Vin	+Vin

NC = No Connection


Notes:

- All dimensions are typical in inches (mm)
- Tolerance x.xx = ±0.01 (±0.25)
- Pin 1 is marked by a "dot" or indentation on the top of the unit

Derating Curve



Mechanical Dimensions



MicroPower Direct
www.micropowerdirect.com

292 Page Street Ste D Stoughton, MA 02072 • TEL: (781) 344-8226 • FAX: (781) 344-8481 • E-Mail: sales@micropowerdirect.com