



1/A

1. No. of pins.
2. Selective plating
- 'G1,—05u" gold over nickel.
- 'G2,—Indicate gold flash.
- 'G3,—10u" gold over nickel.
- 'G4,—15u" gold over nickel.
- 'G5,—30u" gold over nickel.
- 'S1,—05u" Min. gold in contact area/
100u" Min. Tin in solder area.
- 'S2,—Gold flash in contact area/
100u" Min. Tin in solder area.
- 'S3,—10u" Min. gold in contact area/
100u" Min. Tin in solder area.
- 'S4,—15u" Min. gold in contact area/
100u" Min. Tin in solder area.
- 'S5,—30u" Min. gold in contact area/
100u" Min. Tin in solder area.
- 'S6,—50u" Min. gold in contact area/
100u" Min. Tin in solder area.



NOTE 1:

Material Specifications :

1. Plastic Housing : NY-6T UL94V-0 Black Color
2. Terminal : Pho. Bronze 5210

Pating:

1. Signal Pin :
Contact Area : 15u" Gold Plating
Solder Area : 100u"(Min.) Tin Plating
2. Power Pin : 100u"(Min.) Tin Plating

2	Terminal	Phos.Bronze	—	Gold Plated
1	Plastic	NY-6T	BLACK	UL94V-0
NO.	DESCRIPTION	MATERIAL	COLOR	REMARK

SUVIN

CONNECTOR

CUSTOMER COPY	TITLE:2.50mm Pitch Battery Conn
------------------	---------------------------------

	C		C1:增加新料號			Angle	±2°	DRAW	周孫宇	01/10/23	PART NO.		250105MR004XX05ZU ①⑥			
EC1T-020506-03	B	02/05/06	B1:4.60→4.50 ^{+0.10} _{-0.20}	黃能貴	李儒平	30 ~	±0.50									
EC1T-011206-05	A	01/12/06	A1:ADD→GXT電鍍規格	王淑麗	宋權哲	10 ~ 30	±0.30	DESIGN	周孫宇	01/10/23	PART NO. (OLD)		2505A-04GXX-E			
	O	01/11/01	NEW	——	——	~ 10	±0.15	CHECK	陳清照	01/10/23	DRAWING NO. ^D _{ING}		250105MR004XX05ZU			
ECN (DCN) NO.	REV	DATE	DESCRIPTION	CHANGE	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED		APPRO.	宋權哲	01/10/23	SCALE	4:1	UNIT	mm	A4	☉