106SVH400MTP

SURFACE MOUNT

Parts are RoHS compliant

Date code when parts became RoHS: 1608

ELECTRICAL SPECIFICATIONS

Capacitance: 10 uF
Dissipation Factor: 0.25 Max at 120 Hz and 20°C
Temperature Range: -25°C to +105°C
ESR: 41.4466 Ohms Max at 20°C and 120 Hz
Impedance: N/A

Tolerance: -20 %, +20 %
WVDC: 400 Volts DC
SVDC: 450 Volts DC
Ripple Current: 50 mA at 120 Hz and 105°C
Impedance Ratios:-25°C/20°C 4 and - -

Leakage Current: .01CV or 3uA, whichever is greater
40 uA after 2 Minutes

Load Life: 2000 hours at 105°C with 100 % of rated voltage and with 0 % of rated ripple current
Capacitance Change: ≤30% of initial measured value
Dissipation Factor: ≤300% of maximum specified value
Leakage Current: ≤100% of maximum specified value

Frequency Multipliers:

50 HZ	120 HZ	400 HZ	1 KHZ	10 KHZ	100 KHZ
0.7	1	1.17	1.36	1.5	1.5

Temperature Multipliers:

45°C	60°C	70°C	65°C	75°C	85°C	105°C	125°C
2	1.9	1.7	1.8	1.4	1.4	1	0

PHYSICAL DIMENSIONS

Diameter (D): 12.5 mm + 0.5 mm
Length (L): 13.5 mm + 0.5 mm
Lead Spacing (S): 4.4 mm +/- 0.2 mm

Lead Wire Diameter (d): 0.9 mm +/- 0.2 mm
Lead Length: 4.8 mm +/- 0.2 mm
Lead Finish: Matte Tin



3757 W. Touhy Ave. Lincolnwood, IL 60712 (847) 675-1760 FAX (847) 673-2850
Illinois Capacitor (HK) Ltd., Tel: 85227930931, Fax: 85227930731, www.illcap.com.hk
© Copyright 2017 Illinois Capacitor. A division of Cornell Dublier, All Rights Reserved