

ZWS75BAF-3/A





Sales Region	Worldwide	
Series	ZWS-BAF	
Status	Production	
Feature		
Option	With cover type	
Option Lineup	Please refer to here.	
Recommended EMC Filter	Please refer to here.	
Accessories	Please refer to the catalog	



Electrical Characteristics		
Input Voltage Range[AC]	85 to 265V	
Input Voltage Range[DC]	120 to 370V	
Efficiency	78% Typ.	
Rated Output Voltage[DC]	3.3V	
Output Voltage Range[DC]	2.97 to 3.63V	
Maximum Output Current	15A	
Maximum Output Power	49.5W	

Cases Shape & Size		
Case' shape	PC board	
Width(W)	60mm Nom.	
Height(H)	45mm Nom.	
Depth(D)	180mm Nom.	
Weight	380g Typ.	

Other		
Operating Temp. Range	-10 to 60°C	
Cooling	Convection cooling	
	UL60950-1	
Cafaba Chandand (Cantifical)	CSA C22.2 No.60950-1	
Safety Standard(Certified)	EN60950-1	
	EN50178 (OV II)	
Safety Standard(Conformed)	Den-an	
	This page only shows representative characteristics. Please refer to the	
Remarks	technical data for detailed specifications and conditions.	

[!] Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

[!] All specifications are subject to change without notice.