

LWT50H-522



Sales Region	Worldwide
Series	LWT-H
Status	Production
Feature	
Option	
Option Lineup	
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 265V		
Input Voltage Range[DC]	110 to 330V		
Efficiency	72% Typ.		
Rated Output Voltage[DC]	<u>+5V</u> <u>+12V</u> <u>-12V</u>		
Output Voltage Range[DC]	+5 to +5.25V	Fixed	Fixed
Minimum Output Current	<u>1A</u>	<u>0A</u>	<u>0A</u>
Maximum Output Current	<u>8A</u>	<u>1A</u>	<u>1A</u>
Maximum Average Current			
Maximum Peak Current			
Total Maximum(Average) Output Power	50W		
Total Maximum Peak Power			

Cases Shape & Size

Case'□' shape	Unit
Width(W)	97mm Nom.
Height(H)	26mm Nom.
Depth(D)	160mm Nom.
Weight	400g Typ.

Other

Operating Temp. Range	0 to 60°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 EN60950-1
Safety Standard(Conformed)	

