

Part Number: C2409A

Revision

Date:

7/12/2012

**2C/14 19/.0147TC UNSH PVC / PVC****COMMUNICATION & CONTROL CABLE****A. CONSTRUCTION**

Conductor: 14 AWG 19/.0147 TC  
Insulation: .030" Wall, Polyvinyl Chloride  
Cable Core: 2C @ 6.00" LHL  
Jacket: .032" Wall, Polyvinyl Chloride (PVC)  
Print Legend: **CAROL (R) 14 AWG -- C2409A -- 75C E60233-8 (UL)  
CL3 OR AWM STYLE 2587 --- CSA LL69381 CMH --  
MADE IN USA (Date code) (Seq Footage)**

**DIAMETERS**

.071" nom  
.131" nom  
.262" nom  
.326" nom

**B. INDUSTRY APPROVALS**

|                          |                |
|--------------------------|----------------|
| National Electrical Code | Article 725    |
| UL Standard 13           | Type CL3       |
| UL Standard 758          | AWM Style 2587 |
| CSA International        | Type CMH       |

**C. ELECTRICAL PROPERTIES**

|                            |                      |
|----------------------------|----------------------|
| Temperature:               | 75C                  |
| Suggested Working Voltage: | 300V                 |
| Conductor DCR:             | 2.7 Ohms/1000 ft nom |
| Mutual Capacitance:        | 29 pF/ft @ 1kHz nom  |

**D. COLOR CODE**

| Cond | COLOR |
|------|-------|
| 1    | BLACK |
| 2    | WHITE |