
Ultrabright White LED, Ø 3 mm



FEATURES

- Clear, untinted lens
- Utilizing ultrabright InGaN technology
- High luminous intensity
- Luminous intensity and color categorized for each packing unit
- ESD-withstand voltage: up to 2 kV according to JESD22-A114-B
- Compliant to RoHS directive 2002/95/EC

Pb-free

e3

RoHS COMPLIANT

DESCRIPTION

The VLHW4100 is a clear, untinted 3 mm LED for high end applications where supreme luminous intensity is required.

These lamps utilize the highly developed ultrabright InGaN technologies.

The lens and the viewing angle is optimized to achieve best performance of light output and visibility.

APPLICATIONS

- Interior and exterior lighting
- Outdoor LED panels
- Instrumentation and front panel indicators
- Replaces incandescent lamps
- Light guide compatible

PRODUCT GROUP AND PACKAGE DATA

- Product group: LED
- Package: 3 mm
- Product series: standard
- Angle of half intensity: ± 22.5°

PARTS TABLE

PART	COLOR, LUMINOUS INTENSITY	TECHNOLOGY
VLHW4100	White, I_V = (4500 to 11 250) mcd	InGaN and converter

ABSOLUTE MAXIMUM RATINGS VLHW4100 (T_{amb} = 25 °C, unless otherwise specified)

PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
Reverse voltage		V_R	5	V
DC forward current		I_F	25	mA
Peak forward current	at 1 kHz, t_p/T = 0.1	I_{FSM}	0.1	A
Power dissipation		P_V	95	mW
Junction temperature		T_j	120	°C
Operating temperature range		T_{amb}	- 40 to + 95	°C
Storage temperature range		T_{stg}	- 40 to + 100	°C
Soldering temperature	t ≤ 5 s	T_{sd}	260	°C
Thermal resistance junction/ ambient		R_{thJA}	400	K/W

OPTICAL AND ELECTRICAL CHARACTERISTICS (T_{amb} = 25 °C, unless otherwise specified)
WHITE VLHW4100

PARAMETER	TEST CONDITION	PART	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous intensity	I_F = 20 mA	VLHW4100	I_V	4500	7150	11 250	mcd
Chromaticity coordinate x acc. to CIE 1931	I_F = 20 mA		x		0.33		
Chromaticity coordinate y acc. to CIE 1931	I_F = 20 mA		y		0.33		
Angle of half intensity	I_F = 20 mA		φ		± 22.5		deg
Forward voltage	I_F = 20 mA		V_F	2.8	3.2	3.8	V
Reverse current	V_R = 5 V		I_R			50	µA
Temperature coefficient of V_F	I_F = 20 mA		TC_{VF}		- 4		mV/K
Temperature coefficient of I_V	I_F = 20 mA		TC_{IV}		- 0.5		% / K

CHROMATICITY COORDINATED CLASSIFICATION

	X	Y			X	Y
YU	0.274	0.301		WL	0.317	0.325
	0.283	0.284			0.319	0.310
	0.307	0.316			0.329	0.319
	0.303	0.333			0.329	0.336
YL	0.283	0.284		VU	0.329	0.354
	0.290	0.270			0.329	0.336
	0.310	0.299			0.345	0.350
	0.307	0.316			0.347	0.368
XU	0.303	0.333		VL	0.329	0.336
	0.307	0.316			0.329	0.319
	0.317	0.325			0.343	0.331
	0.315	0.343			0.345	0.350
XL	0.307	0.316		UU	0.347	0.368
	0.310	0.299			0.345	0.350
	0.319	0.310			0.361	0.365
	0.317	0.325			0.364	0.383
WU	0.315	0.343		UL	0.345	0.350
	0.317	0.325			0.343	0.331
	0.329	0.336			0.357	0.343
	0.329	0.354			0.361	0.365

Note:
Chromaticity coordinate groups are tested at a current pulse direction of 25 ms and a tolerance of ± 0.01.

LUMINOUS INTENSITY CLASSIFICATION

GROUP	LIGHT INTENSITY (mcd)	
STANDARD	MIN.	MAX.
Z1	4500	5600
Z2	5600	7150
AA	7150	9000
AB	9000	11 250

Note:
Luminous intensity is tested with an accuracy of ± 15 %.
The above type Numbers represent the order groups which include only a few brightness groups. Only one group will be shipped on each reel (there will be no mixing of two groups on each reel). In order to ensure availability, single brightness groups will not be orderable.
In a similar manner for colors where color groups are measured and binned, single color groups will be shipped on any one reel.
In order to ensure availability, single color groups will not be orderable.

TYPICAL CHARACTERISTICS (T_{amb} = 25 °C, unless otherwise specified)




Figure 1. Forward Current vs. Ambient Temperature




Figure 4. Forward Current vs. Forward Voltage




Figure 2. Relative Luminous Intensity vs. Angular Displacement




Figure 5. Relative Luminous Flux vs. Forward Current




Figure 3. Relative Intensity vs. Wavelength






Figure 6. Coordinates of Colorgroups

PACKAGE DIMENSIONS in millimeters






technical drawings
according to DIN
specifications

Not indicated tolerances ± 0.25

Drawing-No.: 6.544-5403.01-4
Issue: 2; 18.06.10
21948

BAR CODE PRODUCT LABEL (example)



A) Type of component
B) Manufacturing plant
C) SEL - selection code (bin):
e.g.: EA = code for luminous intensity group
4C = code for chromaticity coordinate
1 = code for forward voltage
D) Date code year/week
E) Day code (e.g. 1: Monday)
F) Batch no.
G) Total quantity
H) Company code

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.