




SPECIFICATIONS

FREQUENCY RANGE: 2 TO 4 GHz

ISOLATION: 18

LOSS (dB) MIN: 0.6

VSWR MAX: 1.30:1

FORWARD POWER: 10 WATT

REVERSE POWER: 10 WATT

INPUT CONNECTOR: N TYPE

OUTPUT CONNECTOR: N TYPE



PASTERNACK ENTERPRISES, INC.

P.O. BOX 16759, IRVINE, CA 92623
PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: www.pasternack.com
E-MAIL ADDRESS: sales@pasternack.com

COAXIAL & FIBER OPTICS

DWG TITLE

PE8311

DES. N FEMALE ISOLATOR, 2 - 4 GHz, 10W

REV. B

FSCM NO. 53919

CAD FILE 042508

SCALE N/A

SIZE A 127

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.
4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $\pm 3/8"$, WHICHEVER IS GREATER.