


SPECIFICATIONS

1. Current Rating: 1A AC, DC
2. Voltage Rating: 50V AC, DC
3. Temperatur Range: -25°C ~ +85°C
4. Contact Resistance: 20mΩ Max
5. Insulation Resistance: 100mΩ Min
6. Withstanding Voltang: 500V AC/minute
7. Material: Wafer LCP, UL94-V0
PIN Phosphoric bronze Tin-plated
Solder tad Phosphoric bronze Tin-plated

Circuit	Part NO.	Dimensions mm	
		A	B
2	HC-1.0-2PWT-X	1.00	4.30
3	HC-1.0-3PWT-X	2.00	5.30
4	HC-1.0-4PWT-X	3.00	6.30
5	HC-1.0-5PWT-X	4.00	7.30
6	HC-1.0-6PWT-X	5.00	8.30
7	HC-1.0-7PWT-X	6.00	9.30
8	HC-1.0-8PWT-X	7.00	10.30
9	HC-1.0-9PWT-X	8.00	11.30
10	HC-1.0-10PWT-X	9.00	12.30
11	HC-1.0-11PWT-X	10.00	13.30
12	HC-1.0-12PWT-X	11.00	14.30
13	HC-1.0-13PWT-X	12.00	15.30
14	HC-1.0-14PWT-X	13.00	16.30
15	HC-1.0-15PWT-X	14.00	17.30
16	HC-1.0-16PWT-X	15.00	18.30

Ordering Information



			GENERAL TOLERANCE	制图 DRAWING	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
			DIM TOL	审核 CHECK	产品名称 TITLE	1.0 卧贴	版本 REV.	A
			X.X ±0.30	批准 APPROVAL	产品料号 PART NO.	HC-1.0-NPWT-X	单位 UNITS	mm
1	初版发行		X.XX ±0.20	比例 SCALE			页次 SHEET	1/1
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	X.XXX ±0.10	投影 Projection	材料 MATERIAL			
			Angle ±3.0°					