

D



C

B

A

VERSION A

	927839-5	C	CuFe2	vorversilbert PRESILVERED	0.2 - 0.5 FLK	E = 2.2	H = 3.7	0.20mm ² = 1.13	MQC - Applicator 878426-2	539635-1 WITH DIE: mit Matrize 539744-2	2.5	3.8	6.6	19.5	0.3		
	927839-4	C	CuSn4			G = 2.2	K = 3.8	0.25mm ² = 1.15									
	927839-3	C	CuSn4	vorverzinkt PRETINNED		D = 0.8	D = 2.0	0.35mm ² = 1.19									
	927839-2	C	CuSn4		0.5 - 1.0 FLK	E = 2.8	H = 4.5	0.5mm ² = 1.38	MQC - Applicator 2-541689-2	539733-2 WITH DIE: mit Matrize 734249-0	3	4.2	5.8	19.5	0.4		
	927839-1	C	CuFe2	vorversilbert PRETINNED		G = 3.0	K = 4.7	0.75mm ² = 1.47									
	927827-2	C	CuSn4			D = 1.1	D = 2.4	1.0mm ² = 1.56									
	927833-5	D	CuFe2		>1.0 - 2.5 FLK	E = 3.8	H = 5.7	1.5mm ² = 1.76	MQC - Applicator 878367-2	539635-1 WITH DIE: mit Matrize 539733-2	3.5	4.7	6.3	19.5	0.4		
	927833-2	D	CuSn4	vorverzinkt PRETINNED		G = 4.1	K = 5.8	2.0mm ² = 1.90									
	927833-1	D	CuFe2			D = 1.6	D = 3.6	2.5mm ² = 2.04									
	927824-2	C	CuSn4		>2.5 - 4.0 FLK	E = 4.6	H = 6.3	3.0mm ² = 2.13	MQC - Applicator 2-878314-2	539635-1 WITH DIE: mit Matrize 539736-2	4	5.2	6.8	19.5	0.6		
	927824-1	C	CuFe2	vorverzinkt PRETINNED		G = 4.8	K = 6.6	3.5mm ² = 2.24									
	927824-1	C	CuFe2			D = 2.4	D = 4.0	4.0mm ² = 2.35									
	963709-5	C	CuFe2	vorversilbert PRESILVERED	4.0 - 6.0 FLK	E = 5.2	H = 7.3	4.0mm ² = 2.17	MQC - Applicator 2-878738-2	-	4.2	5.6	7.7	20	0.6		
	963709-4	C	CuSn4			G = 5.5	K = 7.6	5.0mm ² = 2.36									
	963709-3	C	CuSn4	vorverzinkt PRETINNED		D = 2.9	D = 4.5	6.0mm ² = 2.55									
	963709-2	C	CuSn4		0.2 - 0.5 FLR	E = 2.2	H = 2.8	0.2mm ² = 1.13	MQC - Applicator 878427-2	-	2.5	3.8	6.4	19.5	0.3		
	1241818-6	B	CuNiSi			G = 2.2	K = 2.8	0.35mm ² = 1.19									
	1241818-5	B	CuFe2			D = 0.8	D = 1.4	0.5mm ² = 1.26									
	1241818-1	B	CuFe2	vorverzinkt PRETINNED		E = 2.8	H = 3.9	0.5mm ² = 1.43			3	4.2	5.8	19.5	0.4		
	927840-5	C	CuFe2	vorversilbert PRESILVERED		G = 3.0	K = 4.1	0.75mm ² = 1.52									
	927840-4	C	CuSn4			D = 1.1	D = 1.8	1.0mm ² = 1.61									
	927840-3	C	CuSn4		>1.0 - 2.5 FLR	E = 3.8	H = 4.8	1.25mm ² = 1.69	MQC - Applicator 878356-2	WITH DIE: mit Matrize 734251-0	3.5	4.7	6.3	19.5	0.4		
	927840-2	C	CuSn4	vorverzinkt PRETINNED		G = 4.1	K = 4.9	1.5mm ² = 1.76									
	1-927831-5	C	CuFe2			D = 1.6	D = 2.6	2.5mm ² = 2.04									
	927831-5	C	CuFe2	vorversilbert PRESILVERED		E = 4.6	H = 5.5	3.0mm ² = 2.13			4	5.2	6.8	19.5	0.6		
	927831-4	C	CuSn4			G = 4.8	K = 5.7	3.5mm ² = 2.24									
	927831-3	C	CuSn4	vorverzinkt PRETINNED		D = 2.4	D = 3.3	4.0mm ² = 2.35									
	927831-2	C	CuSn4		>2.5 - 4.0 FLR	E = 2.8	H = 3.9	0.5mm ² = 1.43	MQC - Applicator 2-878384-2	WITH DIE: mit Matrize 734251-0	4	5.2	6.8	19.5	0.6		
	927831-1	C	CuFe2	vorversilbert PRESILVERED		G = 3.0	K = 4.1	0.75mm ² = 1.52									
	927831-1	C	CuFe2			D = 1.1	D = 1.8	1.0mm ² = 1.61									
	1-927837-5	C	CuFe2			E = 3.8	H = 4.8	1.25mm ² = 1.69									
	927837-6	D	CuFe2			G = 4.1	K = 4.9	1.5mm ² = 1.76									
	927837-3	D	CuSn4	vorversilbert PRESILVERED		D = 1.6	D = 2.6	2.5mm ² = 2.04									
	927837-2	D	CuSn4	vorverzinkt PRETINNED	>2.5 - 4.0 FLR	E = 4.6	H = 5.5	3.0mm ² = 2.13	MQC - Applicator 2-878384-2	WITH DIE: mit Matrize 734251-0	4	5.2	6.8	19.5	0.6		
	927837-1	D	CuFe2			G = 4.8	K = 5.7	3.5mm ² = 2.24									
	1-927829-5	D	CuFe2			D = 2.4	D = 3.3	4.0mm ² = 2.35									
	927829-5	D	CuFe2			E = 2.8	H = 3.9	0.5mm ² = 1.43									
	927829-2	D	CuSn4	vorverzinkt PRETINNED		G = 3.0	K = 4.1	0.75mm ² = 1.52									
	927829-1	D	CuFe2			D = 1.1	D = 1.8	1.0mm ² = 1.61									

VERSION B		2-927836-2	C	CuSn4		0.5 - 1.0 FLR	E = 2.8 G = 3.0 D = 1.1	H = 7.6 K = 7.7 D = 5.6	0.5mm ² = 1.43 0.75mm ² = 1.52 1.0mm ² = 1.61	MQC - Applicator 878337-2	539635-1 WITH DIE: mit Matrize 739736-2	3	5.4	7.2	20	1.25	963243-1 963244-1	100132-1				
		1-927836-2	C	CuFe2															vorverzinkt PRETINNED			
		927836-1	C	CuFe2																		
		2-927835-2	C	CuSn4		>1.0 - 2.5 FLR	E = 3.8 G = 4.1 D = 1.6	H = 7.6 K = 7.7 D = 5.6	1.5mm ² = 1.76 2.0mm ² = 1.90 2.5mm ² = 2.04	MQC - Applicator 878338-2	539635-1 WITH DIE: mit Matrize 539736-2	3.5	5.9	7.7	20	1.25	963244-1 963245-1	100132-1				
		2-927835-1	C	CuSn4																		
		1-927835-3	C	CuFe2																		
		1-927835-2	C	CuFe2		>2.5 - 4.0 FLR	E = 4.6 G = 4.8 D = 2.4	H = 7.6 K = 7.7 D = 5.6	3.0mm ² = 2.13 - 4.0mm ² = 2.35	MQC - Applicator 878441-2	539635-1 WITH DIE: mit Matrize 539736-2	4	5.9	7.7	20	1.25	963245-1	100132-1				
		927835-2	C	CuSn4	vorverzinkt PRETINNED																	
		927835-1	C	CuFe2																		
		2-928966-2	D	CuSn4																		
		2-928966-1	D	CuSn4																		
		1-928966-3	D	CuFe2																		
		1-928966-2	D	CuFe2		1241962-1	B	CuFe2	vorverzinkt PRETINNED	>3.0 - 5.0 FLR	E = 4.8 G = 5.2 D = 2.5	H = 8.15 K = 7.8 D = 6.0	3.0mm ² = 2.25 4.0mm ² = 2.50 5.0mm ² = 2.75	MQC - Applicator -	WITH DIE: mit Matrize	4	5.9	7.7	20	1.25	967011-1 963245-1	100132-1
		928966-2	D	CuSn4	vorverzinkt PRETINNED																	
		928966-1	D	CuFe2																		
		TE Connectivity ORDER - NO STRIP FORM Bandware	REV	MATERIAL Werkstoff	SURFACE Oberflaeche	DGB WIRE RANGE (mm 2)	WIRE CRIMP Drahtcrimp	INSUL-CRIMP Isol - crimp	CRIMP HEIGHT Crimp-Hoehe	APPLICATION TOOL Anschlag-WKZ	HAND TOOL Handzange	A	B	C	D	E	SINGLE WIRE SEAL Einzeldichtung	DEAD END PLUG Blindstopfen	TE CONNECTIVITY ORDER - No.			
					CRIMP DIMENSIONS (mm) Crimpabmessungen (mm)						EXTRACTION TOOL Ausdruckwerkzeug Nr.:726503-1											

CONTACT ZONE SELECTIVE
PRE SILVER PLATED MIN 3-4.5 µm
Kontaktzone selektiv
vorversilbert min. 3-4.5 µm