




ISOCOM
COMPONENTS

ISP06, ISP25, ISP40, ISP60

DESCRIPTION

The ISP06, ISP25, ISP40 and ISP60 are Single Channel Solid State Relays (Photo MOSFET) each consists of an infrared emitting diode optically coupled to a high voltage output detector. The detector consists of a Photo Voltaic Diode Array and high voltage output MOSFETs.

This Single Channel Output configuration is equivalent to 1 Form A of Electro-mechanical Relay.



FEATURES

- Normally Open Single Pole Single Throw Relay
- High Output Voltages 60V to 600V
- Low ON Resistance
- Low Operating Current
- High AC Isolation Voltage 5000V_{RMS}
- Wide Operating Temperature Range
- -40°C to 85°C
- Pb Free and RoHS Compliant
- Safety Approvals Pending

APPLICATIONS

- Industrial Controls
- Telephone/Exchange Equipment
- Measurement Equipment
- FA/OA Equipment
- Security System
- Reed Relay Replacement

ORDER INFORMATION

- Add G after PN for 10mm lead spacing
- Add SM after PN for Surface Mount,
- Add SMT&R after PN for Surface Mount Tape & Reel

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C)

Input Diode

Forward Current	50mA
Reverse Voltage	5V
Forward Peak Current (f=100Hz, Duty Cycle = 0.1%)	1A
Power dissipation	75mW

Output

	ISP06	ISP25	ISP40	ISP60
Output	60	250	400	600
Breakdown Voltage V _L (V)				
Load Current I _L				
Continuous (mA)	550	180	120	50
Pulse (A)	1.2	0.5	0.3	0.15
(100ms, 1 shot, V _L = DC)				
Power Dissipation			500mW	

Total Package

Isolation Voltage (R.H. = 40% - 60%, 1 min)	5000V _{RMS}
Total Power Dissipation	550mW
Operating Temperature	-40 to 85 °C
Storage Temperature	-40 to 125 °C
Lead Soldering Temperature (10s)	260°C

ISOCOM COMPONENTS 2004 LTD

Unit 25B, Park View Road West, Park View Industrial Estate
Hartlepool, Cleveland, TS25 1UD, United Kingdom
Tel: +44 (0)1429 863 609 Fax : +44 (0)1429 863 581
e-mail: sales@isocom.co.uk
<http://www.isocom.com>

ISOCOM COMPONENTS ASIA LTD

Hong Kong Office,
Block A, 8/F, Wah Hing Industrial mansion,
36 Tai Yau Street, San Po Kong, Kowloon, Hong Kong.
Tel: +852 2995 9217 Fax : +852 8161 6292
e-mail sales@isocom.com.hk



ISP06, ISP25, ISP40, ISP60

Truth Table

Input	Output
ON	CLOSE
OFF	OPEN

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

INPUT

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
Forward Voltage	V_F	$I_F = 10\text{mA}$		1.18	1.5	V
Reverse Current	I_R	$V_R = 5\text{V}$			1	μA

OUTPUT

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
Off State Leakage Current	I_{leak}	$I_F = 0\text{mA}$, $V_L = \text{Max}$			1	μA
On Resistance	$R_{d(\text{ON})}$	$I_F = 10\text{mA}$, $I_L = \text{Max}$, $t = 1\text{s}$				Ω
		ISP06		0.7	2.5	
		ISP25		6.5	15	
		ISP40		20	30	
		ISP60		40	70	
Output Capacitance	C_{out}	$V_L = 0\text{V}$, $f = 1\text{MHz}$				pF
		ISP06		85		
		ISP25		60		
		ISP40		45		
		ISP60		30		




ISP06, ISP25, ISP40, ISP60

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

COUPLED

Parameter	Symbol	Test Condition	Min	Typ.	Max	Unit
LED Turn On Current	$I_{F(\text{on})}$	$I_L = \text{Max}$		2.5	5	mA
LED Turn Off Current	$I_{F(\text{off})}$	$I_L = \text{Max}$	0.4	2.5		mA
Turn On Time	T_{on}	$I_F = 10\text{mA}$, $I_L = \text{Max}$, $R_L = 200\Omega$ ISP06 ISP25 ISP40 ISP60		1.4 1.2 0.4 1.4	3 3 3 3	ms
Turn Off Time	T_{off}	$I_F = 10\text{mA}$, $I_L = \text{Max}$, $R_L = 200\Omega$ ISP06 ISP25 ISP40 ISP60		0.05 0.05 0.05 0.05	0.5 0.5 0.5 0.5	ms
Isolation Resistance	R_{L-O}	$V_{L-O} = 500\text{VDC}$	5×10^{10}			Ω
Isolation Capacitance	C_{L-O}	$V = 0\text{V}$, $f = 1\text{MHz}$		1.5		pF

Turn on / Turn off Time





ISP06, ISP25, ISP40, ISP60




Fig 1a Load Current vs Ambient Temperature




Fig 1b Load Current vs Ambient Temperature




Fig 2a On Resistance vs Ambient Temperature




Fig 2b On Resistance vs Ambient Temperature




Fig 3a Load Current vs Load Voltage




Fig 3b Load Current vs Load Voltage



ISP06, ISP25, ISP40, ISP60




Fig 4 LED Turn On Current vs T_A




Fig 5 LED Turn Off Current vs T_A




Fig 6a Turn On Time vs LED Forward Current




Fig 6b Turn On Time vs LED Forward Current




Fig 7 Turn Off Time vs LED Forward Current




Fig 8 Switching Time vs Ambient Temperature



ISP06, ISP25, ISP40, ISP60




Fig 9 LED Dropout Voltage vs T_A




Fig 10 Off State Leakage Current vs Load Voltage




Fig 11 Output Capacitance vs Applied Voltage




ISP06, ISP25, ISP40, ISP60

ORDER INFORMATION

ISP06, ISP25, ISP40, ISP60			
After PN	PN	Description	Packing quantity
None	ISP06, ISP25, ISP40, ISP60	Standard DIP4	100 pcs per tube
G	ISP06G, ISP25G, ISP40G, ISP60G	10mm Lead Spacing	100 pcs per tube
SM	ISP06SM, ISP25SM, ISP40SM, ISP60SM	Surface Mount	100 pcs per tube
SMT&R	ISP06SMT&R, ISP25SMT&R, ISP40SMT&R, ISP60SMT&R	Surface Mount Tape & Reel	1000 pcs per reel

DEVICE MARKING






ISP06 denotes Device Part Number (ISP06 is used as example)
I denotes Isocom
Y denotes 1 digit Year code
WW denotes 2 digit Week code






ISP06, ISP25, ISP40, ISP60

PACKAGE DIMENSIONS (mm)




DIP



G Form




SMD






ISP06, ISP25, ISP40, ISP60

RECOMMENDED PAD LAYOUT FOR SMD (mm)



TAPE AND REEL PACKAGING



Direction of feed from reel




Dimension No.	A	B	Do	D1	E	F
Dimension (mm)	10.4±0.1	4.55±0.1	1.5±0.1	1.5±0.05	1.75±0.1	7.5±0.1
Dimension No.	Po	P1	P2	t	W	K
Dimension (mm)	4.0±0.1	12.0±0.1	2.0±0.1	0.33±0.1	16.0+0.3/ -0.1	4.55±0.1




ISP06, ISP25, ISP40, ISP60

IR REFLOW SOLDERING TEMPERATURE PROFILE (One Time Reflow Soldering is Recommended)




Profile Details	Conditions
Preheat - Min Temperature (T_{SMIN}) - Max Temperature (T_{SMAX}) - Time T_{SMIN} to T_{SMAX} (t_s)	150°C 200°C 60s - 120s
Soldering Zone - Peak Temperature (T_P) - Liquidous Temperature (T_L) - Time within 5°C of Actual Peak Temperature ($T_P - 5^\circ\text{C}$) - Time maintained above T_L (t_L) - Ramp Up Rate (T_L to T_P) - Ramp Down Rate (T_P to T_L)	260°C 217°C 30s 60s - 100s 3°C/s max 6°C/s max
Average Ramp Up Rate (T_{smax} to T_P)	3°C/s max
Time 25°C to Peak Temperature	8 minutes max



ISP06, ISP25, ISP40, ISP60

NOTES :

- Isocom is continually improving the quality, reliability, function or design and Isocom reserves the right to make changes without further notices.
- The products shown in this publication are designed for the general use in electronic applications such as office automation equipment, communications devices, audio/visual equipment, electrical application and instrumentation.
- For equipment/application where high reliability or safety is required, such as space applications, nuclear power control equipment, medical equipment, etc., please contact our sales representatives.
- When requiring a device for any "specific" application, please contact our sales for advice.
- The contents described herein are subject to change without prior notice.
- Do not immerse device body in solder paste.



DISCLAIMER

ISOCOM is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing ISOCOM products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such ISOCOM products could cause loss of human life, bodily injury or damage to property.

In developing your designs, please ensure that ISOCOM products are used within specified operating ranges as set forth in the most recent ISOCOM products specifications.

___ The ISOCOM products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These ISOCOM products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury (“Unintended Usage”). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation Instruments, traffic signal instruments, combustion control instruments, medical Instruments, all types of safety devices, etc.. Unintended Usage of ISOCOM products listed in this document shall be made at the customer’s own risk.

___ Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.

— The products described in this document are subject to the foreign exchange and foreign trade laws.

___ The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by ISOCOM Components for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of ISOCOM Components or others.

The information contained herein is subject to change without notice.