



## SMA Male to SMA Male Precision Cable 48 Inch Length Using 160 Series Coax, RoHS

### TECHNICAL DATA SHEET

PE300-48

#### SMA Male to SMA Male Precision Cable 48 Inch Length Using 160 Series Coax, RoHS

##### Configuration

Connector 1	SMA Male
Connector 2	SMA Male
Cable Type	160 Series

##### Electrical Specifications

Frequency Range, GHz	DC to 18
Impedance, Ohms	50
Maximum VSWR	1.4:1
Velocity of Propagation, %	69.5
RF Shielding, dB	90
Maximum Operating Voltage, Vrms	1,200

##### Typical Electrical Specifications

###### Frequency 1

Frequency, GHz	2
VSWR	1.04:1
Insertion Loss	0.21 dB/ft [ 0.69 dB/m ]

###### Frequency 2

Frequency, GHz	6
VSWR	1.07:1
Insertion Loss	0.3 dB/ft [ 0.98 dB/m ]

###### Frequency 3

Frequency, GHz	10
VSWR	1.11:1
Insertion Loss	0.4 dB/ft [ 1.31 dB/m ]

###### Frequency 4

Frequency, GHz	14
VSWR	1.18:1
Insertion Loss	0.5 dB/ft [ 1.64 dB/m ]

###### Frequency 5

Frequency, GHz	16
VSWR	1.25:1
Insertion Loss	0.55 dB/ft [ 1.8 dB/m ]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Precision Cable 48 Inch Length Using 160 Series Coax, RoHS PE300-48](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



## SMA Male to SMA Male Precision Cable 48 Inch Length Using 160 Series Coax, RoHS

### TECHNICAL DATA SHEET

PE300-48

#### Frequency 6

Frequency, GHz	18
VSWR	1.28:1
Insertion Loss	0.6 dB/ft [ 1.97 dB/m ]

#### Electrical Specification Notes:

Short lengths up to 24" long may exhibit VSWR measurements up to 9% higher.

### Mechanical Specifications

#### Cable Assembly

Cable Type	160 Series
------------	------------

#### Temperature

Temperature Operating Range, deg C	-48 to +204
------------------------------------	-------------

#### Size

Length, in [cm]	48 [121.92]
Diameter, in [mm]	0.17 [4.32]
Weight, lbs [g]	0.038 [17.24]
Cable Color	Blue
One Time Minimum Bend Radius, in [mm]	1 [25.4]

#### Cable

Center Conductor Type	Solid
Cable Inner Conductor	Copper Clad Steel, Silver
No of Shields	3
Dielectric Type	PTFE
Jacket Material	FEP
Jacket Diameter, in [mm]	0.163 [4.14]

#### Connector 1

Type	SMA Male
Configuration	Straight
Inner Conductor Material and Plating	Gold
Coupling Nut Material and Plating	Passivated Stainless Steel
Hex Size, in.	5/16
Torque, in-lbs [Nm]	8 [0.9]
Body Material and Plating	Passivated Stainless Steel
Dielectric Type	PTFE

#### Connector 2

Type	SMA Male
Configuration	Straight
Inner Conductor Material and Plating	Gold

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Precision Cable 48 Inch Length Using 160 Series Coax, RoHS PE300-48](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



## SMA Male to SMA Male Precision Cable 48 Inch Length Using 160 Series Coax, RoHS

### TECHNICAL DATA SHEET

PE300-48

Coupling Nut Material and Plating	Passivated Stainless Steel
Hex Size, in.	5/16
Torque, in-lbs [Nm]	8 [0.9]
Body Material and Plating	Passivated Stainless Steel
Dielectric Type	PTFE

**Compliance Certifications** (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)  
RoHS Compliant Yes

#### Plotted and Other Data

Notes: Values at 25 °C, sea level

SMA Male to SMA Male Precision Cable 48 Inch Length Using 160 Series Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMA Male to SMA Male Precision Cable 48 Inch Length Using 160 Series Coax, RoHS PE300-48](http://www.pasternack.com/sma-male-sma-male-300-series-cable-assembly-pe300-48-p.aspx)

URL: <http://www.pasternack.com/sma-male-sma-male-300-series-cable-assembly-pe300-48-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

