ADELS contact

## Fused Connectors

# 900 SI RZ/ 3 DS



Screw-screwless-Terminal Block, 3 pole, Wire Protector (DS): yes, Fixing: Catch Pin, Voltage Rating: 400 V, Current Rating: 6.3 A

## Order Info

| | |
|---|---|
| **Reference Number (ref. no.)** | 175303 |
| **Applications** | Lighting, Electrical Appliances |
| **PU** | 200 |

## Type

| | |
|---|---|
| **Type** | Screw-screwless-Terminal Block |
| **Number of poles** | 3 pole |
| **Clamping Units per Pole** | 4 |
| **Colour** | white |
| **Connection Type** | Screw-screwless |
| **Wire Protector (DS)** | yes |

## Technical Data

| | |
|---|---|
| **Voltage Rating** | 400 V |
| **Current Rating** | 6.3 A |
| **Insulating Material** | PA 6.6 |
| **Contact Material** | Brass |
| **Flammability Rating** | V-2 |
| **max. Ambient Temperature Operation** | 70 °C |
| **Assembly Contact Screw** | 0.8x4.0 / ↻ 0.5 Nm |
| **Internal Core Cross-Section max.** | 1.5 $mm^2$ |
| **External Core Cross-Section min.** | 0.5 $mm^2$ |
| **External Core Cross-Section max.** | 2.5 $mm^2$ |
| **Internal Stripping Length** | 7.0-7.5 mm |
| **External Stripping Length** | 8.0-8.5 mm |
| **Fixing** | Catch Pin |
| **Internal Core Cross-Section min.** | 0.5 $mm^2$ |
| **Type of Conductor Solid External** | yes |
| **Type of Conductor Flexible External** | yes |
| **Type of Conductor Solid Internal** | yes |
| **Type of Conductor Stranded Internal** | yes |

## Accessories

| | |
|---|---|
| **ZEL 110** | 196420 |