


玻璃放电管 Glass Discharge Tube



目录编号 Catalog No.	直流击穿电压 DC Spark Over Voltage (100v/s)V	冲击击穿电压 Impulse Spark Over Voltage (1kv/ μ s)V	绝缘电阻 Insulation Resistance M Ω	极间电容 Electrode Capacitance 1MHz 0.5V PF	耐冲击电流 Impulse Discharge Current (8/20 μ s 10 times)
G3L140	140 \pm 30%	\leq 500	\geq 100	\leq 1	1.5KA
G3L200	200 \pm 20%	\leq 600	\geq 100	\leq 1	1.5KA
G3L300	300 \pm 20%	\leq 900	\geq 100	\leq 1	1KA
G3L400	400 \pm 20%	\leq 1000	\geq 100	\leq 1	1KA
G3L500	500 \pm 20%	-	\geq 100	\leq 1	1KA
G3L600	600 \pm 20%	-	\geq 100	\leq 1	1KA
G3L101	1000 \pm 20%	-	\geq 100	\leq 1	1KA

- 参考执行标准: ITU-T K.12, GB/T9043-2008 《通信设备过电压保护用气体放电管通用技术条件》。

Reference executive standard: ITU-T K.12, GB/T9043-2008 《General Technical Requirements of Gas Discharge Tubes for the Over-voltage protection of telecommunications installations》.

- 极间电容测试频率为1MHz, 测试电压为0.5V。

The electrode capacitance test frequency is 1MHz and test voltage is 0.5V.

工作与储存温度 Operating and Storage temperature

-40°C ~ 85°C

包装 Packaging

产品采用编带卷盘包装, 2500PCS/盘, 每包装箱包装25000PCS。

Automaton taped 2500PCS per reel, 25000PCS per carton.

Shanghai Leiditech Electronic Co.,Ltd

Email: sale1@leiditech.com

Tel : +86- 021 50828806

Fax : +86- 021 50477059