

- ◆ CMOS Low Power Consumption
- ◆ Oscillation Frequency 4MHz to 125MHz
 - 4MHz to 30MHz (Fundamental Oscillation)
 - 20MHz to 125MHz (3rd Overtone Oscillation)
- ◆ 3 State Output
- ◆ Built-in Capacitors C_g , C_d
- ◆ Built-in Feedback Resistor
- ◆ Chip form
- ◆ Mini Mold SOT-26 Package

GENERAL DESCRIPTION

The XC2164 series are high frequency, low current consumption CMOS ICs with built-in crystal oscillator and divider circuits.


For fundamental oscillation, output is selectable from any one of the following values for f_0 : $f_0/1$, $f_0/2$, $f_0/4$, $f_0/8$.

With oscillation capacitors and a feedback resistor built-in, it is possible to configure a stable fundamental oscillator or 3rd overtone oscillator using only an external crystal.

Also available is an external oscillation capacitor / external oscillation feedback resistor type which makes oscillation frequency control possible.

The XC2164 series are integrated into SOT-26 packages. The series is also available in chip form.

PIN CONFIGURATION



SOT-26 (TOP VIEW)

APPLICATIONS

- Crystal Oscillation Modules
- Micro computer, DSP Clocks
- Communication Equipment
- Various System Clocks

FEATURES

Oscillation Frequency:	4MHz to 30MHz (Fundamental) 20MHz to 125MHz (3rd Overtone)
Divider Ratio:	Selectable from $f_0/1$, $f_0/2$, $f_0/4$, $f_0/8$. ($f_0/2$, $f_0/4$, $f_0/8$ are fundamental only)
Output:	3-State
Operating Voltage Range:	$3.3V \pm 10\%$, $5.0V \pm 10\%$
Low Power Consumption:	Stand -by function included Selectable from C/E type and O/E type
Chip Form:	Chip Size 1.3×0.8 mm
Ultra Small Package:	SOT-26 mini mold

PIN ASSIGNMENT


PIN NUMBER	PIN NAME	FUNCTION
1	Q0	Clock Output
2	VSS	Ground
3	XT	Crystal Oscillator Connection (Output)
4	XT	Crystal Oscillator Connection (Input)
5	VDD	Power Supply
6	INH	Stand-by Control*

* Stand-by control pin has a pull-up resistor built-in.


/INH, Q0 PIN FUNCTION

/INH	Q0
"H" or OPEN	Clock Output
"L"	High Impedance

BLOCK DIAGRAM



Built-in oscillation capacitors, oscillation feedback resistor



External oscillation capacitors, oscillation feedback resistor

ORDERING INFORMATION

XC2164①②③④⑤⑥

DESIGNATOR	SYMBOL	DESCRIPTION		DESIGNATOR	SYMBOL	DESCRIPTION
①	Ratio Divider & Stand-By Mode		③	1	Duty Level	
	A	f0/1 Chip Enable			CMOS (VDD/2)	
	B	f0/2 Chip Enable			Note : TTL : Fundamental 4MHz to 30MHz	
	C	f0/4 Chip Enable	④	Recommended Frequency Range & Rf, Cg, Cd values		
	D	f0/8 Chip Enable		Built-in Type (3rd O/T) =refer to table 1		
	K	f0/1 Output Enable		Built-in Type (Fundamental) =refer to table 2		
	L	f0/2 Output Enable				
	M	f0/4 Output Enable				
	N	f0/8 Output Enable				
	Note : f0/2, f0/4, f0/8 are fundamental only		⑤	Package		
		C		Chip Form		
		M		SOT-26		
②	5	Fixed Number	⑥	R	Embossed Tape: Standard Feed	
				L	Embossed Tape: Reverse Feed	
				T	Chip Tray	
				W	Wafer	

Table 1: Built-in Type (3rd O/T)

SYMBOL	Frequency Range		Rf (kΩ)	Cg (pF)	Cd (pF)
	3.3V ± 10%	5.0V ± 10%			
A	-	20MHz to 30MHz	9.0	21.5	21.5
B	20MHz to 30MHz	30MHz to 40MHz	6.5	20.0	20.0
C	30MHz to 40MHz	40MHz to 50MHz	5.0	16.0	16.0
D	40MHz to 50MHz	50MHz to 65MHz	3.5	14.0	14.0
E	50MHz to 65MHz	65MHz to 80MHz	2.8	12.5	12.5
F	65MHz to 80MHz	80MHz to 95MHz	2.5	10.0	10.0
H	80MHz to 95MHz	95MHz to 110MHz	2.2	8.0	8.0
K	95MHz to 110MHz	110MHz to 125MHz	2.0	7.0	7.0
L	110MHz to 125MHz	-	2.3	5.5	5.5

Table 2 : Built-In Type (Fundamental)

SYMBOL	Frequency Range		Rf (*) (MΩ)	Cg (pF)	Cd (pF)
	3.3V ± 10%	5.0V ± 10%			
M, V	4MHz to 30MHz	4MHz to 30MHz	3.5	35.0	35.0
			7.0		
T	4MHz to 30MHz	4MHz to 30MHz	3.5	20.0	20.0
			7.0		

(*) Rf=3.5MΩ @VDD=5.0V Operation
Rf=7.0MΩ @VDD=3.3V Operation

■ ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	CONDITIONS	UNITS
Supply Voltage	VDD	Vss - 0.3 to Vss + 7.0	V
Input Voltage	VIN	Vss - 0.3 to VDD + 0.3	V
Continuous Total Power Dissipation	Pd	250*	mW
Operating Ambient Temperature	Topr	-40 ~ +85	°C
Storage Temperature	Tstg	-65 ~ +150 (Chip Form)	°C
		-55 ~ +125 (SOT-26)	°C

*When implemented on a glass epoxy PCB (SOT26 package)

■ ELECTRICAL CHARACTERISTICS

XC2164A51M, T, V Fundamental

5.0V Operation (unless otherwise stated, VDD=5.0V, No Load, Ta=30 ~ + 80°C)

PARAMETER	SYMBOL	CONDITIONS		MIN.	TYP.	MAX.	UNITS
Operating Supply Voltage	VDD			4.5	5.0	5.5	V
"H" Level Input Voltage	VIH			2.4			V
"L" Level Input Voltage	VIL					0.4	V
"H" Level Output Voltage	VOH	CMOS : VDD -= 4.5V, IOH= - 16mA		3.9	4.2		V
"L" Level Output Voltage	VOL	CMOS : VDD = 4.5V, IOH=16mA			0.3	0.4	V
Consumption Current 1	IDD1	/INH=Open, Q0=Open f=30MHz	XC2164A51M, V		11	(15)	mA
			XC2164A51T		11	(15)	
Consumption Current 2	IDD2	/INH= " L ", Q0=Open f=30MHz	XC2164A51M, V		5	(8)	μA
			XC2164A51T		5	(8)	
Input pull up resistance 1	Rup1	/INH="L"		0.5	1.0	2.0	MΩ
Input pull up resistance 2	Rup2	/INH=0.7VDD		25	50	100	kΩ
Internal Oscillation Capacitance	Cg	(*)	XC2164A51M, V		35		pF
			XC2164A51T		20		
	Cd	(*)	XC2164A51M, V		35		
			XC2164A51T		20		
Internal Oscillation Feedback Resistance	Rf				3.5		MΩ
Output Disable Leakage Current	IOZ	/INH="L"				10	μA

note 1 : the values for Cg, Cd are the designed values.

XC2164A51M Fundamental

3.3V Operation (unless otherwise stated, VDD=3.3V, No Load, Ta=30 ~ + 80°C)

PARAMETER	SYMBOL	CONDITIONS		MIN.	TYP.	MAX.	UNITS
Operating Supply Voltage	VDD			2.97	3.30	3.63	V
"H" Level Input Voltage	VIH			2.4			V
"L" Level Input Voltage	VIL					0.4	V
"H" Level Output Voltage	VOH	CMOS : 2.97V, IOH= - 8mA		2.5			V
"L" Level Output Voltage	VOL	CMOS : 2.97V, IOH=8mA				0.4	V
Consumption Current 1	IDD1	/INH=Open, Q0=Open f=30MHz	XC2164A51M, V		5	(8)	mA
			XC2164A51T		4	(6.5)	
Consumption Current 2	IDD2	/INH= " L ", Q0=Open f=30MHz	XC2164A51M, V		2	(4)	μA
			XC2164A51T		2	(4)	
Input pull up resistance 1	Rup1	/INH="L"		1.0	2.0	4.0	MΩ
Input pull up resistance 2	Rup2	/INH=0.7VDD		35	70	140	kΩ
Internal Oscillation Capacitance	Cg	(*)	XC2164A51M, V		35		pF
			XC2164A51T		20		
	Cd	(*)	XC2164A51M, V		35		
			XC2164A51T		20		
Internal Oscillation Feedback Resistance	Rf				7.0		MΩ
Output Diable Leakage Current	IOZ	/INH="L"				10	μA

* note 1 : the values for Cg, Cd are the designed values.

■ ELECTRICAL CHARACTERISTICS (Continued)

XC2164A51T, V Fundamental

3.3V Operation (unless otherwise stated, VDD=3.3V, No Load, Ta=30 ~ + 80°C)

PARAMETER	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNITS
Operating Supply Voltage	VDD		2.5	3.30	3.63	V
"H" Level Input Voltage	VIH		2.4			V
"L" Level Input Voltage	VIL				0.4	V
"H" Level Output Voltage	VOH	CMOS : 2.97V, IOH= - 8mA	2.5			V
"L" Level Output Voltage	VOL	CMOS : 2.97V, IOH=8mA			0.4	V
Consumption Current 1	IDD1	/INH=Open, Q0=Open f=30MHz	XC2164A51M, V	5	(8)	mA
			XC2164A51T	4	(6.5)	
Consumption Current 2	IDD2	/INH= " L ", Q0=Open f=30MHz	XC2164A51M, V	2	(4)	μA
			XC2164A51T	2	(4)	
Input pull up resistance 1	Rup1	/INH="L"	1.0	2.0	4.0	MΩ
Input pull up resistance 2	Rup2	/INH=0.7VDD	35	70	140	kΩ
Internal Oscillation Capacitance	Cg	(*)	XC2164A51M, V	35		pF
			XC2164A51T	20		
	Cd	(*)	XC2164A51M, V	35		
			XC2164A51T	20		
Internal Oscillation Feedback Resistance	Rf			7.0		MΩ
Output Diabie Leakage Current	IOZ	/INH="L"			10	μA

* note 1 : the values for Cg, Cd are the designed values.

Comparative Chart of Oscillation Frequency vs. Supply Voltage, and Negative Resistance Value (The designed value when 300MHz Crystal is used.)

SYMBOL	OSCILLATION FREQUENCY vs. SUPPLY VOLTAGE		NEGATIVE RESISTANCE VALUE	
	VDD = 3.3 V, ±10%	VDD = 5.0 V, ±10%	VDD = 3.3V	VDD = 5.0V
M	± 4.3 ppm	± 4.5 ppm	- 130 Ω	- 220 Ω
V	± 1.2 ppm	± 2.1 ppm	- 150 Ω	- 250 Ω
T	± 9.4 ppm	± 7.0 ppm	- 660 Ω	- 760 Ω

ELECTRICAL CHARACTERISTICS (Continued)

XC2164A51A ~ XC2164A51L 3rd Overtone

5.0 Operation (Unless otherwise stated, VDD=5.0V, No Load, Ta=30 ~ + 80°C)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Operating Supply Voltage	VDD		4.5	5.0	5.5	V
"H" Level Input Voltage	VIH		2.4			V
"L" Level Input Voltage	VIL				0.4	V
"H" Level Output Voltage	VOH	CMOS : VDD = 4.5V, IOH= - 16mA	3.9	4.2		V
"L" Level Output Voltage	VOL	CMOS : VDD = 4.5V, IOH=16mA		0.3	0.4	V
Consumption Current 1	IDD1	/INH = Open, Q0 = Open	XC2164A51A, f0=30MHz	17.0	(23)	mA
			XC2164A51B, f0=40MHz	17.0	(23)	
			XC2164A51C, f0=55MHz	19.0	(26)	
			XC2164A51D, f0=70MHz	23.0	(32)	
			XC2164A51E, f0=85MHz	24.0	(32)	
			XC2164A51F, f0=100MHz	30.0	(40)	
			XC2164A51H, f0=110MHz	30.0	(40)	
			XC2164A51K, f0=125MHz	30.0	(40)	
Consumption Current 2	IDD2	/INH="L", Q0=Open		5.0	(8)	μA
Input Pull Up Resistance 1	Rup1	/INH="L"	0.5	1.0	2.0	MΩ
Input Pull Up Resistance 2	Rup2	/INH=0.7VDD	25	50	100	kΩ
Internal Oscillation Feedback Resistance	Rf	XC2164A51A		9.0		kΩ
		XC2164A51B		6.5		
		XC2164A51C		5.0		
		XC2164A51D		3.5		
		XC2164A51E		2.8		
		XC2164A51F		2.5		
		XC2164A51H		2.2		
		XC2164A51K		2.0		
Output Disable Leakage Current	Ioz	/INH="L"			10	μA

XC2164A51A ~ XC2164A51L 3rd Overtone

3.3V Operation (Unless otherwise stated, VDD=3.3V, No Load, Ta=30 ~ + 80°C)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Operating Supply Voltage	VDD		2.97	3.30	3.63	V
"H" Level Input Voltage	VIH		2.4			V
"L" Level Input Voltage	VIL				0.4	V
"H" Level Output Voltage	VOH	CMOS : VDD = 2.97V, IOH= - 8mA	2.5			V
"L" Level Output Voltage	VOL	CMOS : VDD = 2.97V, IOH=8mA			0.4	V
Consumption Current 1	IDD1	/INH = Open, Q0 = Open	XC2164A51B, f0=30MHz	4.5	(7)	mA
			XC2164A51C, f0=40MHz	5.0	(8)	
			XC2164A51E, f0=70MHz	8.0	(13)	
			XC2164A51F, f0=85MHz	8.5	(13)	
			XC2164A51H, f0=100MHz	9.5	(15)	
			XC2164A51K, f0=110MHz	10.0	(15)	
			XC2164A51L, f0=125MHz	10.5	(15)	
Consumption Current 2	IDD2	/INH="L", Q0=Open		2.0	(4)	μA
Input Pull Up Resistance 1	Rup1	/INH="L"	1.0	2.0	4.0	MΩ
Input Pull Up Resistance 2	Rup2	/INH=0.7VDD	35	70	140	kΩ
Internal Oscillation Feedback Resistance	Rf	XC2164A51A		6.5		kΩ
		XC2164A51B		5.0		
		XC2164A51C		3.5		
		XC2164A51D		2.8		
		XC2164A51E		2.5		
		XC2164A51F		2.2		
		XC2164A51H		2.0		
		XC2164A51K		2.3		
Output Disable Leakage Current	Ioz	/INH="L"			10	μA

ELECTRICAL CHARACTERISTICS (Continued)

XC2164A51D 3.3V Operation (Unless otherwise stated, VDD=3.3V, Oscillation Frequency f0=48MHz, No Load, Ta=-30 ~ + 80°C)

PARAMETER	SYMBOL	CONDITIONS	STANDARD VALUES			UNITS	CIRCUITS
			MIN	TYP	MAX		
Operating Voltage	VDD		2.70	3.30	3.63	V	
'H' Level Input Voltage	VIH		2.4			V	①
'L' Level Input Voltage	VIL				0.4	V	①
'H' Level Output Voltage	VOH	CMOS : 2.97V, IOH = - 8mA	2.5			V	②
'L' Level Output Voltage	VOL	CMOS : 2.97V, IOH = 8mA			0.4	V	②
Supply Current 1	IDD1	/INH=Open, Q0=Open XC2164A51D, F0=55MHz		6.5	(10)	mA	③
Supply Current 2	IDD2	/INH = 'L', Q0=Open		2.0		μA	③
Input Pull-Up Resitance 1	Rup1	/INH = 'L'	1.0	2.0	4.0	MΩ	④
Input Pull-Up Resitance 2	Rup2	/INH = 0.7VDD	35	70	140	kΩ	④
Internal Oscillation Feedback Resistance	Rf	XC2164A51D		3.5		kΩ	⑤
Output Disable Leakage Current	Ioz	/INH = 'L'			10	μA	⑥

SWITCHING CHARACTERISTICS

XC2164A51M, T, V Fundamental (Unless otherwise stated, VDD=3.3V or 5.0V, No Load, Ta=30 ~ + 80°C)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Rise Time (note 1)	tr	CMOS: CL=15pF 0.1VDD→0.9VDD		1.5		ns
		TTL : Load=10TTL, 0.4V →2.4V		1.5		ns
Output Fall Time (note 1)	tf	CMOS: CL=15pF 0.9VDD→0.1VDD		1.5		ns
		TTL : Load=10TTL, 2.4V →0.4V		1.5		ns
Output Duty Cycle	DUTY	CMOS: CL=15pF @ 0.5VDD	45		55	%
		TTL : Load=10TTL, 1.4V	45		55	%

note 1 : the values for tr, tf are the designed values.


XC2164A51A ~ XC2164A51L 3rd Overtone (Unless otherwise stated, VDD=3.3V or 5.0V, No Load, Ta=30 ~ + 80°C)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Rise Time (note 1)	tr	CMOS: CL=15pF 0.1VDD→0.9VDD		1.5		ns
Output Fall Time (note 1)	tf	CMOS: CL=15pF 0.9VDD→0.1VDD		1.5		ns
Output Duty Cycle	DUTY	CMOS: CL=15pF @ 0.5VDD	45		55	%

note 1 : the values for tr, tf are the designed values.

SWITCHING WAVEFORMS

● Switching Time CMOS Output




TTL Output



● Duty Cycle

CMOS Output



TTL Output

