


PV3-5-5



Sales Region	Worldwide
Series	PV
Status	Production
Option	
Option Lineup	
Recommended EMC Filter	
Accessories	Please refer to the catalog



Electrical Characteristics

Rated Input Voltage[DC]	5V
Input Voltage Range[DC]	4.5 to 9V
Efficiency	72% Typ.
Rated Output Voltage[DC]	5V
Output Voltage Range[DC]	5 to 6V
Maximum Output Current	
Maximum Ripple Noise	120mV
Maximum Output Power	3W
Withstanding Voltage1	Input - Output: 500VAC: 1min.
Withstanding Voltage2	
Withstanding Voltage3	

Cases Shape & Size

Case'□ shape	On board/Power module
Width(W)	33mm Nom.
Height(H)	18mm Nom.
Depth(D)	8.5mm Nom.
Weight	4g Typ.
Industry Standard Size	
Terminal Style	SIP

Other

Operating Temp. Range	-20 to 70°C
Isolated / Non-isolated	Isolated
Feature	
Safety Standard(Certified)	
Safety Standard(Conformed)	

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.