


Servo motor EMMS-AS-70-S-HV-RRB-S1

Part number: 1704790

FESTO



Data sheet

Feature	Value
Number of pole pairs	4
Type code	EMMS-AS
Rotor position sensor	Resolver
Rotor position sensor interface	SIN/COS analog signals
Rotor position sensor measuring principle	Inductive
Temperature monitoring	PTC resistor
Max. rotational speed	8200 1/min
Nominal rotary speed	7400 1/min
Brake DC operating voltage	24 V
Insulation protection class	F
Brake power consumption	11 W
Motor constants	0.798 Nm/A
Nominal operating voltage DC	565 V
Motor nominal power	992 W
DC nominal voltage	565 V
Motor nominal current	1.6 A
Phase-phase winding resistance	11.935 Ohm
Winding inductance phase-phase	19.741 mH
Type of winding switch	Star inside
Peak current	7.5 A
Voltage constant, phase-to-phase	48.72 mVmin
Rating class according to EN 60034-1	S1
CE marking (see declaration of conformity)	As per EU EMC directive As per EU low voltage directive
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
Storage temperature	-20 °C ... 60 °C
Relative air humidity	0 - 90 %
Degree of protection	IP65
Ambient temperature	-40 °C ... 40 °C
Certification	RCM compliance mark c UL us - Recognized (OL)
Total output inertia moment	0.46 kgcm ²
Brake holding torque	2 Nm
Brake mass moment of inertia	0.07 kgcm ²
Nominal torque	1.28 Nm
Peak torque	5.17 Nm

Feature	Value
Stall torque	1.62 Nm
Permissible axial shaft load	75 N
Permissible radial shaft load	150 N
MTTF, subcomponent	80 years, rotor position sensor 1769 years, holding brake
MTTFd, subcomponent	160 years, rotor position sensor
Switching cycles, holding brake	10 million idle actuations (without friction work!)
Product weight	2390 g
Electrical connection technology	Plug
Note on materials	RoHS-compliant
Conforms to standard	IEC 60034