



PCB Layout Component Side Shown(6P4C)



NOTES:
Mechanical:
 1. Housing material : High Temp. UL94V-0 , Color: Black
 2. Contact material: Phosphor Bronze t=0.35mm
 3. Contact plating: 6u" Gold on contact area Tin on solder side all over Nickel
 4. Operating Life: 750 Cycles min.
 5. PCB Retention Post-solder: 10 LBS min.
Electrical:
 1. Voltage Rating: 125VAC.
 2. Current Rating: 1.5AMP.
 3. Contact Resistance: 35mΩ max.
 4. Insulation Resistance: 1000MΩ min. @ 500 VDC
 5. Dielectric Strength: 1000 VAC 60Hz, 1 min.
Environmental:
 1. Storage: -40°C To +85°C
 2. Operation: -40°C~+70°C
 3. IR Reflow Soldering Temp: 255°C~265°C(5~10S)
 Packing: 150pcs/Tape reel, 1500pcs/Carton

RoHS compliant
Unit:mm

Scale	Free						Date	Name	Customer-No.
TOLERANCE						Drawn	27.05.2013	Amy	
X.X	±0.20					Approved	27.05.2013	Amy	ASSMANN WSW-No.
X.XX	±0.15								A-2004-0-4-LP/SMT-C
X.XXX	±0.10								Drawing-No.
DIM	TOL								ASS 5690 CO
		①	Drawn	27.05.2013	Amy				rev00
Angle	±5°	Id.	Modification	Date	Name			Replace	SHEET



Customer-No.
 ASSMANN WSW-No.
 A-2004-0-4-LP/SMT-C
 Drawing-No.
ASS 5690 CO
 rev00
 Replace
 SHEET