Pushing Performance

# Han-Yellock F-c 1mm² (Au)



Image is for illustration purposes only. Please refer to product description.

| | |
|---|---|
| Part number | 11 05 000 6224 |
| Specification | Han-Yellock F-c 1mm² (Au) |
| HARTING eCatalogue | https://b2b.harting.com/11050006224 |

## Identification

| | |
|---|---|
| Category | Contacts |
| Series | Han-Yellock® |
| Type of contact | Crimp contact |

## Version

| | |
|---|---|
| Gender | Female |
| Manufacturing process | Turned contacts |

## Technical characteristics

| | |
|---|---|
| Conductor cross-section | 1 mm² |
| Conductor cross-section | AWG 18 |
| Operating current | ≤20 A |
| Contact resistance | ≤2 mΩ |
| Stripping length | 6.5 mm |

## Material properties

| | |
|---|---|
| Material (contacts) | Copper alloy |
| Surface (contacts) | Gold plated |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |


HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany
Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

Pushing Performance

## Material properties

| | |
|---|---|
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | b51e5b97-eeb5-438b-8538-f1771d43c17d |

## Specifications and approvals

| | |
|---|---|
| Specifications | EN 60664-1<br>IEC 61984 |

## Commercial data

| | |
|---|---|
| Packaging size | 100 |
| Net weight | 0.67 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| eCl@ss | 27440204 Contact for industrial connectors |


HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany
Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com