AMETHERM
Circuit Protection Thermistors


DATA SHEET

Part Number: MS32 10015

Ordering Different Lead Types:

Inside Kinked Leads	Not available
Outside Kinked Leads	Use **–B** after Ametherm's Part #

For example: to order an outside kinked lead use part number MS32 10015-**B**



Resistance @ 25°C	10 Ω ± 25%
Max Steady State Current Up to 65°C	15.0 A
Max Recommended Energy Rating	250.0 J
Actual Failure Point of Instantaneous Energy	500.0 J
Resistance @ 100 % of Maximum Current	0.058 Ω
Resistance @ 50% of Maximum Current	0.220 Ω
Body Temperature @ Max Current	224 °C
Dissipation Constant	63.7 mW/°C
Thermal Time Constant	194 seconds
Material Type	"H"
Maximum Capacitance @ 240/440 VAC	1250 µF

D	30.0 ±2.5 mm
T	8.0 ± 1.0 mm
Lead Diameter	1.0 ± 0.1 mm
S	7.8 ± 2.0 mm
L	38.0 ± 9.0 mm
Coating Run Down Straight Leads	5.0 ± 1.0 mm
B	9.30 ± 0.85 mm
C	3.82 ± 1.0 mm

Revision Date 3/16/2004

Ametherm, Inc. 3111 N. Deer Run Road #4 Carson City, NV 89701
Telephone: (800) 808-2434 (775) 884-2434 Fax: (775) 884-0670
www.ametherm.com