




Rev	AWO #	Description	Date	Appr
-		RELEASED	10/26/10	

APPROVED: _____

DATE: _____ TITLE: _____



SPECIFICATIONS:

- Material: Nylon 66, rated UL 94V-0
- Insulator color: Natural
- Contacts: Phosphor Bronze
- Plating: Gold flash over Nickel underplate overall

- Electrical: Current rating: 11 Amps max. Insulation resistance: 1000 Mohms min @ 500 VDC Dielectric withstanding voltage: 5000 VAC for 1 minute
- Mechanical: Temperature Rating: Operating temperature: 0°C to +85°C

- Environmental: Lead free, RoHS compliant.
- Recommended soldering temp: 235°C for 5 sec.



Positions: 6, 9, 12, 15
 A = .250 [6.35] X No. of Positions + .050 [1.27]
 B = .250 [6.35] X No. of Spaces

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE MM [INCHES] TOLERANCES: EXCEPT AS NOTED INCHES			
.X	± .10	ØXX	± .10
.XX	± .020	ØXXX	± .015
.XXX	± .015	ØXXXX	± .010
APPROVALS	DATE		
DRAWN AY	10/26/10		
CHECKED AW	10/26/10		
APPROVED			

ADAM TECH
 909 Rahway Avenue, Union, NJ 07083
 Phone: 908-687-5000 Fax: 908-687-5710

**WIRE TO BOARD, FEMALE, 6.35mm PITCH
 GOLD PLATED**

SIZE	PART NO.	REV.
X	DME-XX-S-SQ-G-V0	-

REF: S00123T SCALE: NTS SHEET 1 OF 2

6 5 4 3 2 1