



Kaga Electronics(USA) Inc.

ADAPTER - 36W / 48W / 60W



FEATURE

	36W	48W	60W
Desktop:IEC 320	C14	C14	C6,C8,C14
Input Range Voltage:90~264Vac,47~63HZ	∨	∨	∨
Output power	36 watt max.	48 watt max	60 watt max
Efficiency 80%typical	∨	∨	∨
Short Circuit Protection	∨	∨	∨
Over Voltage Protection	∨	∨	∨
Leakage current: less than 3.5mA	∨	∨	C6, C14
Leakage current: less than 0.25mA	x	x	C8
Load Regulation ±5%	∨	∨	∨
M.T.B.F.:50,000 hours min.at 25°C,full load	∨	∨	∨
Cable type	UL1185/18AWG	UL1185/18AWG	UL1185/18AWG
Dimension:120(L)×60(W)×38(H)mm	∨	∨	∨
Weight	300g	300g	325g

APPLICATION

LCD Monitor,Notebook,Printer,Portable device

SAFTY & EMI

SAFETY	UL,cUL,GS,PSE, BSMI,CSA,3C	UL,cUL,GS,PSE, BSMI,CSA,N,3C	UL,cUL,GS,PSE, BSMI,3C
EMI	CE Class B, Conduction & Raditac	∨	∨

ENVIRONMENTAL

Operating Temperature: 0 ~ +40°C
 Storage Temperature : -20 ~ +60°C
 Relative Humidity:operating 20 ~ 80%RH
 Storage:10 ~ 90%RH

MODEL

NO	MODEL NAME	Voltage(V)	Current(A)	Power(W)
1	STD-1203	12	3	36
2	STD-1204	12	4	48
3	STD-1205	12	5	60
4	STD-1504	15	4	60
5	STD-1638	16	3.8	60.8
6	STD-1834	18	3.4	61.2
7	STD-1932	19	3.2	60.8
8	STD-2003	20	3	60
9	STD-2227	22	2.7	59.4
10	STD-2425	24	2.5	60
11	STD-2425AF	24	2.5	60

MECHANICAL DRAWING

