

**HF RoHS SIDAct<sup>®</sup> Series - DO-214**



**Agency Approvals**

| AGENCY | AGENCY FILE NUMBER |
|--------|--------------------|
|        | E133083            |

**Pinout Designation**

Not Applicable

**Schematic Symbol**



**Description**

SIDAct<sup>®</sup> Series DO-214AA are designed to protect baseband equipment such as modems, line cards, CPE and DSL from damaging overvoltage transients.

The series provides a surface mount solution that enables equipment to comply with global regulatory standards.

**Features and Benefits**

- Low voltage overshoot
- Low on-state voltage
- Does not degrade with use
- Fails short circuit when surged in excess of ratings
- Low Capacitance

**Applicable Global Standards**

- TIA-968-A
- TIA-968-B
- ITU K.20/21 Enhanced Level\*
- ITU K.20/21 Basic Level
- GR 1089 Inter-building\*
- GR 1089 Intra-building
- IEC 61000-4-5
- YD/T 1082
- YD/T 993
- YD/T 950

\*A/B-rated parts require series resistance

**Electrical Characteristics**

| Part Number | Marking | $V_{DRM}$<br>@ $I_{DRM}=5\mu A$ | $V_S$<br>@ $100V/\mu s$ | $I_H$  | $I_S$  | $I_T$ | $V_T$<br>@ $I_T=2.2$ Amps | Capacitance<br>@ 1MHz, 2V bias |        |
|-------------|---------|---------------------------------|-------------------------|--------|--------|-------|---------------------------|--------------------------------|--------|
|             |         | V min                           | V max                   | mA min | mA max | A max | V max                     | pF min                         | pF max |
| P0080SALRP  | P-8A    | 6                               | 25                      | 50     | 800    | 2.2   | 4                         | 25                             | 150    |
| P0220SALRP  | P22A    | 15                              | 32                      | 50     | 800    | 2.2   | 4                         | 25                             | 150    |
| P0300SALRP  | P03A    | 25                              | 40                      | 50     | 800    | 2.2   | 4                         | 15                             | 140    |
| P0640SALRP  | P06A    | 58                              | 77                      | 150    | 800    | 2.2   | 4                         | 40                             | 60     |
| P0720SALRP  | P07A    | 65                              | 88                      | 150    | 800    | 2.2   | 4                         | 35                             | 60     |
| P0900SALRP  | P09A    | 75                              | 98                      | 150    | 800    | 2.2   | 4                         | 25                             | 55     |
| P1100SALRP  | P11A    | 90                              | 130                     | 150    | 800    | 2.2   | 4                         | 30                             | 50     |
| P1300SALRP  | P13A    | 120                             | 160                     | 150    | 800    | 2.2   | 4                         | 25                             | 45     |
| P1500SALRP  | P15A    | 140                             | 180                     | 150    | 800    | 2.2   | 4                         | 25                             | 40     |
| P1800SALRP  | P18A    | 170                             | 220                     | 150    | 800    | 2.2   | 4                         | 25                             | 35     |
| P2100SALRP  | P21A    | 180                             | 240                     | 150    | 800    | 2.2   | 4                         | 20                             | 35     |
| P2300SALRP  | P23A    | 190                             | 260                     | 150    | 800    | 2.2   | 4                         | 25                             | 35     |
| P2600SALRP  | P26A    | 220                             | 300                     | 150    | 800    | 2.2   | 4                         | 20                             | 35     |
| P3100SALRP  | P31A    | 275                             | 350                     | 150    | 800    | 2.2   | 4                         | 20                             | 35     |
| P3500SALRP  | P35A    | 320                             | 400                     | 150    | 800    | 2.2   | 4                         | 20                             | 35     |
| P0080SBLRP  | P-8B    | 6                               | 25                      | 50     | 800    | 2.2   | 4                         | 25                             | 150    |
| P0220SBLRP  | P22B    | 15                              | 32                      | 50     | 800    | 2.2   | 4                         | 25                             | 150    |
| P0300SBLRP  | P03B    | 25                              | 40                      | 50     | 800    | 2.2   | 4                         | 15                             | 140    |
| P0640SBLRP  | P06B    | 58                              | 77                      | 150    | 800    | 2.2   | 4                         | 40                             | 80     |

Table continues on next page.

**Electrical Parameters** (continued)

| Part Number | Marking | $V_{DRM}$<br>@ $I_{DRM}=5\mu A$ | $V_S$<br>@ 100V/ $\mu s$ | $I_H$  | $I_S$  | $I_T$ | $V_T$<br>@ $I_T=2.2$ Amps | Capacitance<br>@ 1MHz, 2V bias |        |
|-------------|---------|---------------------------------|--------------------------|--------|--------|-------|---------------------------|--------------------------------|--------|
|             |         | V min                           | V max                    | mA min | mA max | A max | V max                     | pF min                         | pF max |
| P0720SBLRP  | P07B    | 65                              | 88                       | 150    | 800    | 2.2   | 4                         | 35                             | 75     |
| P0900SBLRP  | P09B    | 75                              | 98                       | 150    | 800    | 2.2   | 4                         | 35                             | 70     |
| P1100SBLRP  | P11B    | 90                              | 130                      | 150    | 800    | 2.2   | 4                         | 30                             | 70     |
| P1300SBLRP  | P13B    | 120                             | 160                      | 150    | 800    | 2.2   | 4                         | 25                             | 60     |
| P1500SBLRP  | P15B    | 140                             | 180                      | 150    | 800    | 2.2   | 4                         | 25                             | 55     |
| P1800SBLRP  | P18B    | 170                             | 220                      | 150    | 800    | 2.2   | 4                         | 25                             | 50     |
| P2100SBLRP  | P21B    | 180                             | 240                      | 150    | 800    | 2.2   | 4                         | 20                             | 35     |
| P2300SBLRP  | P23B    | 190                             | 260                      | 150    | 800    | 2.2   | 4                         | 25                             | 50     |
| P2600SBLRP  | P26B    | 220                             | 300                      | 150    | 800    | 2.2   | 4                         | 20                             | 45     |
| P3100SBLRP  | P31B    | 275                             | 350                      | 150    | 800    | 2.2   | 4                         | 20                             | 45     |
| P3500SBLRP  | P35B    | 320                             | 400                      | 150    | 800    | 2.2   | 4                         | 20                             | 40     |
| P0080SCLRP  | P-8C    | 6                               | 25                       | 50     | 800    | 2.2   | 4                         | 45                             | 260    |
| P0220SCLRP  | P22C    | 15                              | 32                       | 50     | 800    | 2.2   | 4                         | 30                             | 240    |
| P0300SCLRP  | P03C    | 25                              | 40                       | 50     | 800    | 2.2   | 4                         | 25                             | 250    |
| P0640SCLRP  | P06C    | 58                              | 77                       | 150    | 800    | 2.2   | 4                         | 55                             | 155    |
| P0720SCLRP  | P07C    | 65                              | 88                       | 150    | 800    | 2.2   | 4                         | 50                             | 150    |
| P0900SCLRP  | P09C    | 75                              | 98                       | 150    | 800    | 2.2   | 4                         | 45                             | 140    |
| P1100SCLRP  | P11C    | 90                              | 130                      | 150    | 800    | 2.2   | 4                         | 45                             | 115    |
| P1300SCLRP  | P13C    | 120                             | 160                      | 150    | 800    | 2.2   | 4                         | 40                             | 105    |
| P1500SCLRP  | P15C    | 140                             | 180                      | 150    | 800    | 2.2   | 4                         | 35                             | 95     |
| P1800SCLRP  | P18C    | 170                             | 220                      | 150    | 800    | 2.2   | 4                         | 35                             | 90     |
| P2100SCLRP  | P21C    | 180                             | 240                      | 150    | 800    | 2.2   | 4                         | 30                             | 90     |
| P2300SCLRP  | P23C    | 190                             | 260                      | 150    | 800    | 2.2   | 4                         | 30                             | 80     |
| P2600SCLRP  | P26C    | 220                             | 300                      | 150    | 800    | 2.2   | 4                         | 30                             | 80     |
| P3100SCLRP  | P31C    | 275                             | 350                      | 150    | 800    | 2.2   | 4                         | 30                             | 70     |
| P3500SCLRP  | P35C    | 320                             | 400                      | 150    | 800    | 2.2   | 4                         | 25                             | 65     |

**Notes:**

- Absolute maximum ratings measured at  $T_A = 25^\circ C$  (unless otherwise noted).
- Devices are bi-directional.


**Surge Ratings**

| Series | $I_{PP}$                                     |                                        |                                          |                                            |                                            |                                          |                                            |                                              |                                           | $I_{TSM}$<br>50/60 Hz | di/dt             |
|--------|----------------------------------------------|----------------------------------------|------------------------------------------|--------------------------------------------|--------------------------------------------|------------------------------------------|--------------------------------------------|----------------------------------------------|-------------------------------------------|-----------------------|-------------------|
|        | 0.2x310 <sup>1</sup><br>0.5x700 <sup>2</sup> | 2x10 <sup>1</sup><br>2x10 <sup>2</sup> | 8x20 <sup>1</sup><br>1.2x50 <sup>2</sup> | 10x160 <sup>1</sup><br>10x160 <sup>2</sup> | 10x560 <sup>1</sup><br>10x560 <sup>2</sup> | 5x320 <sup>1</sup><br>9x720 <sup>2</sup> | 10x360 <sup>1</sup><br>10x360 <sup>2</sup> | 10x1000 <sup>1</sup><br>10x1000 <sup>2</sup> | 5x310 <sup>1</sup><br>10x700 <sup>2</sup> |                       |                   |
|        | A min                                        | A min                                  | A min                                    | A min                                      | A min                                      | A min                                    | A min                                      | A min                                        | A min                                     |                       | Amps/ $\mu s$ max |
| A      | 20                                           | 150                                    | 150                                      | 90                                         | 50                                         | 75                                       | 75                                         | 45                                           | 75                                        | 20                    | 500               |
| B      | 25                                           | 250                                    | 250                                      | 150                                        | 100                                        | 100                                      | 125                                        | 80                                           | 100                                       | 25                    | 500               |
| C      | 50                                           | 500                                    | 400                                      | 200                                        | 150                                        | 200                                      | 175                                        | 100                                          | 200                                       | 30                    | 500               |


**Notes:**

- 1 Current waveform in  $\mu s$
- 2 Voltage waveform in  $\mu s$
- Peak pulse current rating ( $I_{PP}$ ) is repetitive and guaranteed for the life of the product.
- $I_{PP}$  ratings applicable over temperature range of  $-40^\circ C$  to  $+85^\circ C$
- The device must initially be in thermal equilibrium with  $-40^\circ C \leq T_J \leq +150^\circ C$


## Thermal Considerations

| Package                                                                                       | Symbol          | Parameter                               | Value       | Unit |
|-----------------------------------------------------------------------------------------------|-----------------|-----------------------------------------|-------------|------|
| DO-214AA<br> | $T_J$           | Operating Junction Temperature Range    | -40 to +150 | °C   |
|                                                                                               | $T_S$           | Storage Temperature Range               | -65 to +150 | °C   |
|                                                                                               | $R_{\theta JA}$ | Thermal Resistance: Junction to Ambient | 90          | °C/W |


## V-I Characteristics




## $t_r \times t_d$ Pulse Waveform



## Normalized $V_S$ Change vs. Junction Temperature




## Normalized DC Holding Current vs. Case Temperature



## Soldering Parameters

|                                                        |                                   |                               |
|--------------------------------------------------------|-----------------------------------|-------------------------------|
| Reflow Condition                                       |                                   | Pb-Free assembly (see Fig. 1) |
| Pre Heat                                               | -Temperature Min ( $T_{s(min)}$ ) | +150°C                        |
|                                                        | -Temperature Max ( $T_{s(max)}$ ) | +200°C                        |
|                                                        | -Time (Min to Max) ( $t_s$ )      | 60-180 secs.                  |
| Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak) |                                   | 3°C/sec. Max.                 |
| $T_{s(max)}$ to $T_L$ - Ramp-up Rate                   |                                   | 3°C/sec. Max.                 |
| Reflow                                                 | -Temperature ( $T_L$ ) (Liquidus) | +217°C                        |
|                                                        | -Temperature ( $t_L$ )            | 60-150 secs.                  |
| Peak Temp ( $T_p$ )                                    |                                   | +260(+0/-5)°C                 |
| Time within 5°C of actual Peak Temp ( $t_p$ )          |                                   | 30 secs. Max.                 |
| Ramp-down Rate                                         |                                   | 6°C/sec. Max.                 |
| Time 25°C to Peak Temp ( $T_p$ )                       |                                   | 8 min. Max.                   |
| Do not exceed                                          |                                   | +260°C                        |




## Physical Specifications

|                        |                                                               |
|------------------------|---------------------------------------------------------------|
| <b>Lead Material</b>   | Copper Alloy                                                  |
| <b>Terminal Finish</b> | 100% Matte-Tin Plated                                         |
| <b>Body Material</b>   | UL recognized epoxy meeting flammability classification 94V-0 |


## Environmental Specifications

|                                         |                                                                                                                        |
|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>High Temp Voltage Blocking</b>       | 80% Rated $V_{DRM}$ ( $V_{AC Peak}$ ) +125°C or +150°C, 504 or 1008 hrs. MIL-STD-750 (Method 1040) JEDEC, JESD22-A-101 |
| <b>Temp Cycling</b>                     | -65°C to +150°C, 15 min. dwell, 10 up to 100 cycles. MIL-STD-750 (Method 1051) EIA/JEDEC, JESD22-A-104                 |
| <b>Biased Temp &amp; Humidity</b>       | 52 $V_{DC}$ (+85°C) 85%RH, 504 up to 1008 hrs. EIA/JEDEC, JESD22-A-101                                                 |
| <b>High Temp Storage</b>                | +150°C 1008 hrs. MIL-STD-750 (Method 1031) JEDEC, JESD22-A-101                                                         |
| <b>Low Temp Storage</b>                 | -65°C, 1008 hrs.                                                                                                       |
| <b>Thermal Shock</b>                    | 0°C to +100°C, 5 min. dwell, 10 sec. transfer, 10 cycles. MIL-STD-750 (Method 1056) JEDEC, JESD22-A-106                |
| <b>Autoclave (Pressure Cooker Test)</b> | +121°C, 100%RH, 2atm, 24 up to 168 hrs. EIA/JEDEC, JESD22-A-102                                                        |
| <b>Resistance to Solder Heat</b>        | +260°C, 30 secs. MIL-STD-750 (Method 2031)                                                                             |
| <b>Moisture Sensitivity Level</b>       | 85%RH, +85°C, 168 hrs., 3 reflow cycles (+260°C Peak). JEDEC-J-STD-020, Level 1                                        |


## Part Numbering



## Part Marking



## Dimensions — DO-214AA



| Dimensions | Inches |       | Millimeters |      |
|------------|--------|-------|-------------|------|
|            | Min    | Max   | Min         | Max  |
| A          | 0.130  | 0.156 | 3.30        | 3.95 |
| B          | 0.201  | 0.220 | 5.10        | 5.60 |
| C          | 0.077  | 0.087 | 1.95        | 2.20 |
| D          | 0.159  | 0.181 | 4.05        | 4.60 |
| E          | 0.030  | 0.063 | 0.75        | 1.60 |
| F          | 0.075  | 0.096 | 1.90        | 2.45 |
| G          | 0.002  | 0.008 | 0.05        | 0.20 |
| H          | 0.077  | 0.104 | 1.95        | 2.65 |
| K          | 0.006  | 0.016 | 0.15        | 0.41 |

## Packing Options

| Package Type | Description                  | Quantity | Added Suffix | Industry Standard |
|--------------|------------------------------|----------|--------------|-------------------|
| S            | DO-214AA<br>Tape & Reel Pack | 2500     | RP           | EIA-481-D         |

## Tape and Reel Specification — DO-214AA

