


Fast Diodes, 460 A (SUPER MAGN-A-PAK™ Power Modules)



SUPER MAGN-A-PAK™

FEATURES

- High power FAST recovery diode series
- High current capability
- 3000 V_{RMS} isolating voltage with non-toxic substrate
- High surge capability
- High voltage ratings up to 2500 V
- Industrial standard package
- UL E78996 approved 
- Lead (Pb)-free
- Designed and qualified for industrial level



RoHS
COMPLIANT

PRODUCT SUMMARY

$I_{F(AV)}$	460 A
-------------	-------

TYPICAL APPLICATIONS

- Snubber for large GTO
- Snubber for large IGBT

MAJOR RATINGS AND CHARACTERISTICS

SYMBOL	CHARACTERISTICS	VALUES	UNITS
$I_{F(AV)}$		460	A
	T_C	82	°C
$I_{F(RMS)}$		720	A
	T_C	82	°C
I_{FSM}	50 Hz	13 000	A
	60 Hz	13 800	
I^2t	50 Hz	845	kA ² s
	60 Hz	790	
$I^2\sqrt{t}$		8450	kA ² √s
V_{RRM}	Range	1600 to 2500	V
t_{rr}		4.0	μs
T_{Sig}, T_J	Range	- 40 to 150	°C


ELECTRICAL SPECIFICATIONS

VOLTAGE RATINGS

TYPE NUMBER	VOLTAGE CODE	V_{RRM} , MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE V	V_{RSM} , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE V	I_{RRM} MAXIMUM AT T_J MAXIMUM mA
VSKDL450..S20	16	1600	1700	50
	20	2000	2100	
	25	2500	2600	

FORWARD CONDUCTION							
PARAMETER	SYMBOL	TEST CONDITIONS			VALUES	UNITS	
Maximum average forward current at case temperature	I _{F(AV)}	180° conduction, half sine wave			460	A	
					82	°C	
Maximum RMS forward current	I _{F(RMS)}	180° conduction, half sine wave at T _C = 82 °C			720	A	
Maximum peak, one-cycle forward, non-repetitive surge current	I _{FSM}	t = 10 ms	No voltage reapplied	Sinusoidal half wave, initial T _J = T _J maximum	13.0	kA	
		t = 8.3 ms			13.8		
		t = 10 ms	100 % V _{RRM} reapplied		11.1		
		t = 8.3 ms			11.8		
Maximum I ² t for fusing	I ² t	t = 10 ms	No voltage reapplied		845	kA ² s	
		t = 8.3 ms			790		
		t = 10 ms	100 % V _{RRM} reapplied		616		
		t = 8.3 ms			578		
Maximum I ² √t for fusing	I ² √t	t = 0.1 to 10 ms, no voltage reapplied			8450	kA ² √s	
Low level value of threshold voltage	V _{F(TO)1}	(16.7 % × π × I _{F(AV)} < I < π × I _{F(AV)}), T _J = T _J maximum			1.16	V	
High level value of threshold voltage	V _{F(TO)2}	(I > π × I _{F(AV)}), T _J = T _J maximum			1.62		
Low level value of forward slope resistance	r _{f1}	(16.7 % × π × I _{F(AV)} < I < π × I _{F(AV)}), T _J = T _J maximum			0.68	mΩ	
High level value of forward slope resistance	r _{f2}	(I > π × I _{F(AV)}), T _J = T _J maximum			0.41		
Maximum forward voltage drop	V _{FM}	I _{pk} = 1800 A, T _J = 25 °C, t _p = 10 ms sine pulse			2.20	V	

RECOVERY CHARACTERISTICS							
CODE	MAXIMUM VALUE AT $T_J = 25\text{ °C}$	TEST CONDITIONS			TYPICAL VALUES AT $T_J = 150\text{ °C}$		
	t_{rr} AT 25 % I_{RRM} (μs)	I_{pk} SQUARE PULSE (A)	di/dt (A/μs)	V_r (V)	t_{rr} AT 25 % I_{RRM} (μs)	Q_{rr} (μC)	I_r (A)
S20	2.0	1000	100	- 50	4	400	180



BLOCKING				
PARAMETER	SYMBOL	TEST CONDITIONS	VALUES	UNITS
RMS insulation voltage	V_{INS}	$t = 1\text{ s}$	3000	V
Maximum peak reverse and off-state leakage current	I_{RRM}	$T_J = T_J\text{ maximum}$, rated V_{RRM} applied	50	mA



THERMAL AND MECHANICAL SPECIFICATIONS				
PARAMETER	SYMBOL	TEST CONDITIONS	VALUES	UNITS
Maximum operating junction and storage temperature range	T_J, T_{Stg}		- 40 to 150	°C
Maximum thermal resistance, junction to case per junction	R_{thJC}	DC operation	0.065	K/W
Maximum thermal resistance, case to heatsink	R_{thC-hs}		0.02	
Mounting torque $\pm 10\%$ SMAP to heatsink busbar to SMAP		A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound.	6 to 8	Nm
			12 to 15	
Approximate weight			1500	g
Case style		See dimensions - link at the end of datasheet	SUPER MAGN-A-PAK	

ΔR_{thJC} CONDUCTION				
CONDUCTION ANGLE	SINUSOIDAL CONDUCTION	RECTANGULAR CONDUCTION	TEST CONDITIONS	UNITS
180°	0.009	0.006	$T_J = T_J \text{ maximum}$	K/W
120°	0.011	0.011		
90°	0.014	0.015		
60°	0.021	0.022		
30°	0.037	0.038		

Note

- The table above shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC




Fig. 1 - Current Ratings Characteristics




Fig. 4 - Forward Power Loss Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 3 - Forward Power Loss Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - Forward Power Loss Characteristics




Fig. 8 - Forward Power Loss Characteristics








Fig. 9 - Forward Power Loss Characteristics






ORDERING INFORMATION TABLE

Device code	VSK	D	L	450	-	25	S20
	1	2	3	4		5	6
1	-	Module type					
2	-	Circuit configuration D = 2 diodes in series					
3	-	Fast recovery					
4	-	Current rating					
5	-	Voltage code x 100 = V_{RRM} (see Voltage Ratings table)					
6	-	t_{rr} code (see Recovery Characteristics table)					

CIRCUIT CONFIGURATION



LINKS TO RELATED DOCUMENTS	
Dimensions	http://www.vishay.com/doc?95088



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.