General Cable

Product Data Sheet

RoHS Compliant Directive 2002/95/EC

Part Number: C1704 Revision Level: 11/19/2012

2C 16AWG 26/30BC PP, PVC **COMMAND ® SERIES**

A. CONSTRUCTION

		DIAMETERS
Conductor:	16 AWG 26/30 BC	.057" nom
Insulation:	.009" Wall, Polypropylene (PP)	.075" nom
Cable Core:	2C @ 6.00" LHL	.150" nom
Jacket:	.030" Polyvinyl Chloride (PVC)	.210" nom
Print Legend:	***CAROL ® -- C1704 -- 2C 16AWG COMMAND SERIES AUDIO CABLE (UL) E60233-8 CL3 60C -- CSA C/US CMG 80C OR CSA AWM I/II A/B 80C 600V FT4 -- ROHS -- MADE IN USA (Date code) (Seq Footage)***	

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 444	Type CL3
CSA International	Type AWM I/II A/B

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +80°C
Suggested Working Voltage:	600V Max
Conductor DCR:	4.03 Ohms/M' @ 20°C (nom)
Mutual Capacitance:	21.4 pF/ft @ 1kHz (nom)

D. COLOR CODE

Item	COLOR
1	BLACK
2	RED

E. CUSTOMER APPROVAL

Signature: _____

Date: _____

Note: Data subject to change without notice. Contact your Customer Service representative for latest information.