


ISO cylinder DSBF-C-125-50-PPVA-N3-R

Part number: 1785014

FESTO



Data sheet

Feature	Value
Piston seal material	TPE-U(PU)
Piston rod wiper seal material	TPE-U(PU)
Cushion piston material	POM
Buffer seal material	TPE-U(PU)
Material of piston	Aluminium-Knetlegierung
Nut material	hochlegierter Stahl rostfrei
Flange screws material	Stahl verzinkt
Material of bearing	POM
Stroke	50 mm
Piston diameter	125 mm
Piston rod thread	M27x2
Type code	DSBF
Cushioning	Pneumatic cushioning, adjustable at both ends
Mounting position	Any
Conforms to standard	ISO 15552
Piston rod end	External thread
Design	Piston rod Piston Profile barrel
Position sensing	For proximity sensor
Symbol	00991235
Operating pressure	0.6 bar ... 10 bar
Mode of operation	Double-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	3 - High corrosion stress
Ambient temperature	-20 °C ... 80 °C
Impact energy in the end positions	3.3 J
Cushioning length	45 mm
Theoretical force at 6 bar, retracting	6881 N
Theoretical force at 6 bar, advancing	7363 N
Moving mass at 0 mm stroke	2245 g
Additional weight per 10 mm stroke	163 g
Basic weight with 0 mm stroke	6928 g
Additional moving mass per 10 mm stroke	63 g

Feature	Value
Type of mounting	With accessories With internal thread Optionally:
Pneumatic connection	G1/2
Note on materials	RoHS-compliant
Cover material	Die-cast aluminum
Piston rod material	High-alloy stainless steel
Material of cylinder barrel	Wrought aluminum alloy