



Data

Notes

Note Only required when using relays without integrated status indicator!

Technical data

Operating data

Nominal operating voltage	AC 230 V
Power consumption at U_N	1.6 mA

Signaling

Status indicator	Red LED
------------------	---------

Subject to changes. Please also observe the further product documentation!



Safety and protection

Protection type	IP20
-----------------	------

Mechanical data

Mounting type	Pluggable module
---------------	------------------

Material data

Fire load	0.033 MJ
Weight	1.6 g

Commercial data

Product Group	6 (Interface Electronics)
PU (SPU)	50 (25) Stück
Packaging type	box
Country of origin	DE
GTIN	4045454484644
Customs tariff number	85318070000

Downloads

Documentation

Bid Text

788-125 docx - Datei	2019. 2. 20.	docx 15.4 kB	Download
788-125 X81 - Datei	2019. 2. 19.	xml 2.6 kB	Download

Additional Information

Disposal; Electrical and electronic equipment, Packaging	V 1.0.0	pdf 265.8 kB	Download
--	---------	-----------------	----------

CAD/CAE-Data

CAD data

2D/3D Models 788-125

Subject to changes. Please also observe the further product documentation!



URL Download

CAE data

WSCAD Universe 788-125 URL Download

ZUKEN Portal 788-125 URL Download

EPLAN Data Portal 788-125 URL Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 788-125 URL Download

Accessories for relay modules; Operation status indicator: red

Installation Notes

Subject to changes. Please also observe the further product documentation!