
FAIRCHILD
SEMICONDUCTOR®


6-PIN PHOTOTRANSISTOR OPTOCOUPLERS

SL5500 SL5501 SL5504 SL5511

PACKAGE



SCHEMATIC



DESCRIPTION

The SL5500, SL5501, SL5504 and SL5511 are optically coupled isolators each consisting of an infrared emitting GaAs diode and a silicon NPN phototransistor with accessible base. These devices are housed in 6-pin dual-in-line packages (DIP).

FEATURES

- High output/input DC current transfer ratio
- Low saturation voltage
- High isolation voltage of 5.3 kV RMS
- UL recognized (File # E90700)
- VDE recognized (File # 94766)
  - Ordering option ‘300’ (e.g. SL5500.300)

APPLICATIONS

- Power supply regulators
- Digital logic inputs
- Microprocessor inputs
- Appliance sensor systems
- Industrial controls

© 2003 Fairchild Semiconductor Corporation

Parameters		Symbol	Value	Units
TOTAL DEVICE				
Storage Temperature		T_{STG}	-55 to +150	°C
Operating Temperature		T_{OPR}	-55 to +100	°C
Lead Solder Temperature		T_{SOL}	260 for 10 sec	°C
Total Power Dissipation at T_A = 25°C Ambient		P_D	260	mW
Derate Linearly from 25°C			3.3	mW/°C
EMITTER				
Continuous Reverse Voltage		V_R	3	V
Continuous Forward Current		I_F	100	mA
Forward Current - Peak (10 µs pulse, δ = 0.01)		I_F(pk)	3.0	A
Total Power Dissipation T_A = 25°C Ambient		P_D	150	mW
Derate Linearly from 25°C			2.0	mW/°C
DETECTOR				
Collector to Emitter Voltage (open base)	SL5500, SL5501, SL5511	V_{CEO}	30	V
	SL5504		80	
Collector to Base Voltage (open emitter)	SL5500, SL5501, SL5511	V_{CBO}	70	V
	SL5504		120	
Emitter to Collector Voltage (open base)		V_{ECO}	7	V
Emitter to Base Voltage (open colletor)		V_{EBO}	7	V
DC Collector Current		I_C	100	mA
Detector Power Dissipation @ T_A = 25°C Ambient		P_D	150	mW
Derate Linearly from 25°C			2.0	mW/°C

© 2003 Fairchild Semiconductor Corporation

ELECTRICAL CHARACTERISTICS (T_A = 25°C Unless otherwise specified.)

INDIVIDUAL COMPONENT CHARACTERISTICS

Parameters	Test Conditions	Symbol	Device	Min	Typ*	Max	Units
EMITTER							
Input Forward Voltage	I_F = 20 mA, T_A = 25 to 70°C	V_F	All		1.23	1.3	V
	I_F = 2 mA				1.10	1.2	V
Reverse Current	V_R = 3 V, T_A = 25 to 70°C	I_R	All		0.001	10	µA
DETECTOR	V_{CE} = 10 V	I_{CEO}	All		1	50	nA
Leakage Current Collector to Emitter	V_{CE} = 30 V				0.005	10	µA
	V_{CE} = 10 V, T_A = 70°C					500	nA
	V_{CB} = 30 V	I_{CBO}			0.001	50	µA
Breakdown Voltage Collector to Emitter	I_C = 10 µA, I_F = 0	BV_{CEO}	SL5500, SL5501, SL5511	30	100		V
			SL5504	80	110		
Collector to Base	I_C = 10 µA, I_F = 0	BV_{CBO}	SL5500, SL5501, SL5511	30	120		V
			SL5504	120	150		
Emitter to Collector	I_E = 10 µA, I_F = 0	BV_{ECO}	All	7	10		V
Emitter to Base	I_E = 10 µA, I_F = 0	BV_{EBO}	All	7	10		V

ISOLATION CHARACTERISTICS

Characteristic	Test Conditions	Symbol	Min	Typ*	Max	Units
Input-Output Isolation Voltage (note 1)	f = 60Hz, T = 1 min.	V_{ISO}	5300			$V_{AC(RMS)}$
Isolation Resistance	V_{I-O} = ±500 VDC	R_{ISO}	1	10		TΩ
Isolation Capacitance	f = 1 MHz, V = 0V	C_{ISO}		0.6	1.3	pF

*Typical values at T_A = 25°C

© 2003 Fairchild Semiconductor Corporation

TRANSFER CHARACTERISTICS (TA = 25°C Unless otherwise specified.)							
DC Characteristics	**Test Conditions**	**Symbol**	**Device**	**Min**	**Typ**	**Max**	**Units**
Output/Input Current Transfer Ratio	I_F = 10 mA, V_{CE} = 0.4 V	CTR	SL5500	50		300	%
	I_F = 10 mA, V_{CE} = 0.4 V, T_A = 70°C		SL5500	40		300	
	I_F = 10 mA, V_{CE} = 0.4 V, T_A = 25°C to 70°C		SL5501, SL5504	25		400	
	I_F = 2 mA, V_{CE} = 5 V		SL5500	40			
	I_F = 2 mA, V_{CE} = 5 V, T_A = 70°C		SL5500	30			
	I_F = 2 mA, V_{CE} = 5 V, T_A = 25°C to 70°C		SL5501, SL5504	15			
	I_F = 2 mA, V_{CE} = 5 V, T_A = 25°C to 70°C		SL5511	25			
	I_F = 0.5 mA, V_{CE} = 0.4 V, T_A = 25°C to 70°C		SL5511	20			
Collector-Emitter Saturation Voltage	I_F = 50 mA, I_C = 10 mA	$V_{CE(SAT)}$	SL5500			0.4	V
	I_F = 20 mA, I_C = 2 mA		SL5501, SL5504, SL5511			0.4	
AC Characteristics	**Test Conditions**	**Symbol**	**Device**	**Min**	**Typ**	**Max**	**Units**
Saturated Switching Times							
Turn-On Time	R_L = 1 kΩ, I_F = 16 mA, V_{CC} = 5 V	t_{on}	SL5500, SL5501, SL5511			20	µs
			SL5504			50	
Turn-Off Time	See Fig. 1 and Fig. 2	t_{off}	SL5500, SL5501, SL5511			50	µs
			SL5504			150	

Note

1. Device considered a two-terminal device: pins 1, 2 and 3 shorted together and pins 4, 5 and 6 shorted together.

© 2003 Fairchild Semiconductor Corporation




Fig. 1 Switching Circuit




Fig. 2 Waveforms

Fig. 3 LED Forward Voltage vs. Forward Current




Fig. 4 Normalized CTR vs. Forward Current




Fig. 5 Normalized CTR vs. Ambient Temperature




Fig. 7 CTR vs. RBE (Unsaturated)




Fig. 7 CTR vs. RBE (Saturated)




Fig. 8 Normalized t_{off} vs. R_{BE}




Fig. 9 Normalized t_{on} vs. R_{BE}




Fig. 10 Switching Speed vs. Load Resistor




Fig. 11 Collector Emitter Saturation Voltage vs. Collector Current






Fig. 12 Dark Current vs. Ambient Temperature




© 2003 Fairchild Semiconductor Corporation


Package Dimensions (Through Hole)




Package Dimensions (Surface Mount)



Package Dimensions (0.4” Lead Spacing)



Recommended Pad Layout for Surface Mount Leadform




Note
All dimensions are in inches (millimeters)

© 2003 Fairchild Semiconductor Corporation

ORDERING INFORMATION

Option	Order Entry Identifier	Description
S	.S	Surface Mount Lead Bend
SD	.SD	Surface Mount; Tape and Reel
W	.W	0.4" Lead Spacing
300	.300	VDE 0884
300W	.300W	VDE 0884, 0.4" Lead Spacing
3S	.3S	VDE 0884, Surface Mount
3SD	.3SD	VDE 0884, Surface Mount, Tape and Reel


MARKING INFORMATION



Definitions	
1	Fairchild logo
2	Device number
3	VDE mark (Note: Only appears on parts ordered with VDE option – See order entry table)
4	Two digit year code, e.g., ‘03’
5	Two digit work week ranging from ‘01’ to ‘53’
6	Assembly package code


© 2003 Fairchild Semiconductor Corporation

Carrier Tape Specifications ("D" Taping Orientation)



NOTE
All dimensions are in inches (millimeters)

Reflow Profile (Black Package, No Suffix)



- Peak reflow temperature: 225°C (package surface temperature)
- Time of temperature higher than 183°C for 60–150 seconds
- One time soldering reflow is recommended

© 2003 Fairchild Semiconductor Corporation

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

© 2003 Fairchild Semiconductor Corporation