



DB201S-DB207S


SURFACE MOUNT BRIDGE RECTIFIERS

Features

- Glass Passivated Die Construction
- Low leakage
- Ideal for printed circuit board
- Surge overload rating-30A peak
- Designed for Surface Mount Application
- Plastic Material-UL Flammability 94V-0

Mechanical Data

- Case:Reliable low cost construction utilizing molded plastic technique
- Terminals:Plated Leads Solderable per MIL-STD-202,Method208
- Polarity:As Marked on Case
- Mounting Position:Any
- Marking:Type Number



Maximum Ratings and Electrical Characteristics @TA=25°C unless otherwise specified

Single Phase,half wave,60Hz,resistive or inductive load.For capacitive load,derate current by 20%.

Parameter	Symbol	DB201S	DB202S	DB203S	DB204S	DB205S	DB206S	DB207S	UNIT
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	800	1000	V
Maximum Average forward output rectified current @TA=40℃	I (AV)	2.0							A
Peak forward surge current 8.3ms single sine-wave superimposed on rated load(JEDEC Method)	I _{FSM}	50							A
Maximum instantaneous forward voltage drop per diode @2.0A	V _F	1.1							V
Maximum DC reverse current at TA=25℃ rated DC blocking voltage per leg TA=125℃	I _R	5.0 500							uA
Typical thermal resistance per leg (Note1)	R θ JA	40							℃ /W
	R θ JL	15							
Operating junction temperature range	T _J	-55 to +150							℃
storage temperature range	T _{stg}	-55 to +150							℃

Note:

- 1.Mounted on glass epoxy PC board with 1.3mm² solder pad.
- 2.Mounted on aluminum substrate PC board with 1.3mm² solder pad.
- 3.Measured at 1.0MHz and applied reverse of 4.0V D.C.





DB201S-DB207S

SURFACE MOUNT BRIDGE RECTIFIERS

Characteristic Curves $(T_A=25^\circ\text{C}$ unless otherwise noted)

