

30V N-CHANNEL ENHANCEMENT MODE MOSFET

MAIN CHARACTERISTICS

I_D	80A
V_{DSS}	30V
R_{DSON}-typ(@V_{GS}=10V)	< 4mΩ(Type:3.3 mΩ)





PDFN3*3-8L

Pb lead-free ROHS

Application

- Battery protection
- Load switch
- Uninterruptible power supply

Product Specification Classification

Part Number	Package	Marking	Pack
YFW80N03DF	PDFN3*3-8L	YFW 80N03DF XXXXX	5000PCS/Tape

Maximum Ratings at Tc=25°C unless otherwise specified

Characteristics	Symbols	Value	Units
Drain-Source Voltage	V_{DS}	30	V
Gate - Source Voltage	V_{GS}	±20	V
Continuous Drain Current, V_{GS} @ 10V[1] @T_C=25℃	I_D	80	A
Continuous Drain Current, V_{GS} @ 10V[1]@T_C=100℃	I_D	50	A
Continuous Drain Current, V_{GS} @ 10V[1] @T_A=25℃	I_D	17	A
Continuous Drain Current, V_{GS} @ 10V[1]@T_A=70℃	I_D	14	A
Pulsed Drain Current[2]	I_{DM}	160	A
Single Pulse Avalanche Energy[3]	E_{AS}	144.7	mJ
Avalanche Current	I_{AS}	53.8	A
Total Power Dissipation[4] @T_C=25℃	P_D	43.4	W
Total Power Dissipation[4] @T_A=25℃	P_D	1.67	W
Storage Temperature Range	T_{STG}	-55 to +150	°C
Operating Junction Temperature Range	T_J	-55 to +150	°C
Thermal Resistance, Junction-to-Ambient [1]	$R_{\theta JA}$	75	°C/W
Thermal Resistance Junction-Case[1]	$R_{\theta JC}$	2.88	°C/W

Download from alldatasheet.com

Maximum Ratings at Tc=25°C unless otherwise specified

Characteristics	Test Condition	Symbols	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	V_{GS}=0V, I_D=250uA	BV_{DSS}	30	-	-	V
BVDSS Temperature Coefficient	Reference to 25℃ , ID=1mA	$\Delta BV_{DSS/\Delta TJ}$	-	0.0213	-	V/°C
Static Drain-Source On-Resistance[2]	V_{GS}=10V, I_D=30A	$R_{DS(ON)}$	-	3.3	4.0	mΩ
	V_{GS}=4.5V, I_D=15A		-	5.5	6.5	
Gate -Threshold Voltage	V_{DS}=V_{GS}, I_D=250uA	$V_{GS(th)}$	1.0	1.5	2.5	V
$V_{GS(th)}$ Temperature Coefficient		$V_{GS(th)}$	-	-5.73	-	mV/°C
Drain -Source Leakage Current	V_{DS}=24V , V_{GS}=0V , T_J=25℃	I_{DSS}	-	-	1	μA
	V_{DS}=24V , V_{GS}=0V , T_J=55℃		-	-	5	
Gate-Source Leakage Current	V_{GS}=±20V, V_{DS}=0V	I_{GSS}	-	-	±100	nA
Forward Transconductance	V_{DS}=5V, I_D=30A	g_{FS}	-	26.5	-	S
Gate Resistance	V_{DS}=0V , V_{GS}=0V , f=1MHz	R_g	-	1.4	-	
Total Gate Charge(4.5V)	V_{DS}=20V V_{GS}=4.5V I_D=12A	Q_g	-	31.6	-	nC
Gate-Source Charge		Q_{gs}	-	6.07	-	
Gate-Drain Charge		Q_{gd}	-	13.8	-	
Turn-on delay time	V_{DD}=15V V_{GS}=10V R_G=1.5 I_D=20A	$t_{d(on)}$	-	11.2	-	ns
Rise Time		T_r	-	49	-	
Turn-Off Delay Time		$t_{d(OFF)}$	-	35	-	
Fall Time		t_f	-	7.8	-	
Input Capacitance	V_{DS}=15V V_{GS}=0V f=1.0MHz	C_{iss}	-	3075	-	pF
Output Capacitance		C_{oss}	-	400	-	
Reverse Transfer Capacitance		C_{rss}	-	315	-	
Continuous Source Current[1,5]	V_G=V_D=0V , Force Current	I_S	-	-	80	A
Pulsed Source Current[2,6]		I_{SM}	-	-	160	A
Diode Forward Voltage [2]	V_{GS}=0V , I_S=1A , T_J=25℃	V_{SD}	-	-	1	V

Note :
1.The data tested by surface mounted on a 1 inch2 FR-4 board with 2OZ copper.
2.The data tested by pulsed , pulse width ≦ 300us , duty cycle ≦ 2%
3.The EAS data shows Max. rating . The test condition is VDD=25V,VGS=10V,L=0.1mH,IAS=53.8A
4.The power dissipation is limited by 150℃ junction temperature
5 .The data is theoretically the same as ID and IDM , in real applications , should be limited by total power dissipation.

Download from alldatasheet.com

Ratings and Characteristic Curves

Typical Characteristics




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance vs. G-S Voltage




Fig.3 Forward Characteristics of Reverse




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized $V_{GS(th)}$ vs. T_J




Fig.6 Normalized R_{DSON} vs. T_J

Download from alldatasheet.com

Ratings and Characteristic Curves




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching Time Waveform





Fig.11 Unclamped Inductive Switching Waveform

Download from alldatasheet.com

Package Outline Dimensions Millimeters

PDFN3*3-8L



Symbol	Common		
	mm		
	Mim	Nom	Max
A	0.70	0.75	0.85
A1	/	/	0.05
b	0.20	0.30	0.40
c	0.10	0.152	0.25
D	3.15	3.30	3.45
D1	3.00	3.15	3.25
D2	2.29	2.45	2.65
E	3.15	3.30	3.45
E1	2.90	3.05	3.20
E2	1.54	1.74	1.94
E3	0.28	0.48	0.65
E4	0.37	0.57	0.77
E5	0.10	0.20	0.30
e	0.60	0.65	0.70
K	0.59	0.69	0.89
L	0.30	0.40	0.50
L1	0.06	0.125	0.20
t	0	0.075	0.13
Φ	10	12	14

Download from alldatasheet.com