


<b>Sales Region</b>	Worldwide (except Japan)
<b>Series</b>	PXC-M
<b>Model</b>	PXC-M10
<b>Status</b>	 Production
<b>Option</b>	Pinout style B (No remote ON/OFF & no trim pin)
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	
<b>Accessories</b>	



### Electrical Characteristics

Nominal Input Voltage[DC]	24Vdc
Input Voltage Range[DC]	9 to 36Vdc
Efficiency	83% Typ.
Rated Output Voltage[DC]	3.3Vdc
Output Voltage Range[DC]	Fixed
Output Current Range	0 to 2.5A
Maximum Ripple Noise	30mV
Maximum Output Power	10W
Withstanding Voltage1	Input - Output: 5000AC: 1min.
Withstanding Voltage2	
Withstanding Voltage3	

### Package Type & Size

Package / Mounting	PCB mount
Width(W)	31.8mm Nom. (1.25in Nom.)
Height(H)	10.2mm Nom. (0.40in Nom.)
Depth(D)	20.3mm Nom. (0.80in Nom.)
Weight	14g Typ.
Industry Standard Size	DIP-24
Terminal Style	DIP

### Other

Operating Temp. Range	-40 to 105°C
Isolation	Isolated
Feature	
Safety Standard(Certified)	IEC60950-1 EN60950-1 UL60950-1

Safety Standard(Conformed)

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.

Remarks

This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.